

 DigiWise International Corporation www.digiwise.asia E-mail: sales@digiwise.asia												
Model No.	Resolution	Viewing Direction	Outline Dimension	Active Area	Code : A.B.C.D.xxx means same interface	L (cd/m2)	Temperature 0.T/5.T		BL Power consumption	Touch Panel	Note	Options
13-017FMCB00A0-S	128RGB*160	12(Gray Inversion)	34.7*16.7*2.7	28.03*15.04	MCU0800 interface/SPI 3wire		200	20~70/-30~80		None	MOQ 1K/Lot	
13-022CMCB00A0-S	176RGB*220	12(Gray Inversion)	41.7*56.16*2.25	34.85*43.56	MCU 8080 interface 8/16bit		170	20~70/-30~80		None	MOQ 1K/Lot	
13-024QMTB00A0-S	240RGB*240	12(Gray Inversion)	43.6*61.5*2.28	36.72*48.96	MCU0800 interface		250	20~60/-30~70		None	MOQ 1K/Lot	
13-028QMTB00A0-S	240RGB*320	12(Gray Inversion)	49.8* 69*2.45	43.2* 57.6	MCU parallel / RGB		500	20~70/-30~80		None	MOQ 1K/Lot	
13-028QMTB00A2-S	240RGB*320	12(Gray Inversion)	49.8* 69*2.45	43.2* 57.6	MCU parallel / RGB		300	20~70/-30~80		None	MOQ 1K/Lot	
13-035QMTB00A0-S	320RGB*240	6(Gray Inversion)	76.9*63.9*3.3	70.08*52.56	Parallel RGB-24 bit / 54pin (A)		900	20~70/-30~80	0.372W	None		
13-035QMTB4RA0-S	320RGB*240	6(Gray Inversion)	76.9*63.9*4.4	70.08*52.56	Parallel RGB-24 bit / 54pin (A)		720	20~70/-30~80	0.372W	4-wire RTP		
13-035QMTB8IAA0-S	320RGB*240	6(Gray Inversion)	79.9*68.9*4.9	70.08*52.56	Parallel RGB-24 bit / 54pin (A)		800	20~70/-30~80	0.372W	PCT_I2C	PCT IC_FT5216	
13-035QMTB00A1-S	320RGB*240	6(Gray Inversion)	76.9*63.9*3.3	70.08*52.56	Parallel RGB-24 bit / 54pin (A)		500	20~70/-30~80	0.372W	None		
13-035QMTB4RA1-S	320RGB*240	6(Gray Inversion)	76.9*63.9*4.4	70.08*52.56	Parallel RGB-24 bit / 54pin (A)		400	20~70/-30~80	0.372W	4-wire RTP		
13-035QMTB8IA1-S	320RGB*240	6(Gray Inversion)	76.9*63.9*4.9	70.08*52.56	Parallel RGB-24 bit / 54pin (A)		450	20~70/-30~80	0.372W	PCT_I2C	FT5216	
13-035QMTB00A2-S	320RGB*240	6(Gray Inversion)	76.9*63.9*3.3	70.08*52.56	Parallel RGB-24 bit / 54pin (A)		900	20~70/-30~80	0.372W	None	Anti-Reflection	PI / 4W
13-035QMTB00A3-S	320RGB*240	Free of All	76.9*63.9*3.3	70.08*52.56	Parallel RGB-24 bit / 54pin (A)		700	20~70/-30~80	0.372W	None	Optical Film	PI / 4W
13-035QMTB00A5-S	320RGB*240	6(Gray Inversion)	76.9*63.9*3.3	70.08*52.56	Parallel RGB-24 bit / 54pin (A)		300	20~70/-30~80	0.384W	None		
13-035QMTB00B0-S	320RGB*240	6(Gray Inversion)	76.9*63.9*3.15	70.08*52.56	Parallel RGB-24 bit / 54pin (A)		1500	20~70/-30~80	0.744W	None		
13-035QMTB8IA0-S	320RGB*240	6(Gray Inversion)	76.9*63.9*4.75	70.08*52.56	Parallel RGB-24 bit / 54pin (A)		1300	20~70/-30~80	0.744W	PCT_I2C		
13-040VMSB00GA0-S	480RGB* 800	12 o'clock (Gray Inversion)	57.14*96.85*2.23	51.84*86.4	SPI+ RGB 24bit		400	20~70/-30~80	0.512W	4-wire RTP		
13-040V05B4HA0-S	480RGB* 800	Free of All	57.14*96.85*3.42	51.84*86.4	SPI+ RGB 24bit		250	20~70/-30~80	0.512W	4-wire RTP		
13-043YMTB00A0-S	480RGB*272	6(Gray Inversion)	105.5*67.2*2.9	95.04*53.856	Parallel RGB-24 bit / 40pin (B)		900	20~70/-30~80	0.768W	None		CP
13-043YMTB4RA0-S	480RGB*272	6(Gray Inversion)	105.5*67.2*4.0	95.04*53.856	Parallel RGB-24 bit / 40pin (B)		720	20~70/-30~80	0.768W	4-wire RTP		CP
13-043YMTB8IA0-S	480RGB*272	6(Gray Inversion)	116.04*74.85*4.9	95.04*53.856	Parallel RGB-24 bit / 40pin (B)		800	20~70/-30~80	0.768W	PCT_I2C	FT5306	CP
13-043YMTB00A1-S	480RGB*272	6(Gray Inversion)	105.5*67.2*2.9	95.04*53.856	Parallel RGB-24 bit / 40pin (B)		500	20~70/-30~80	0.768W	None		CP
13-043YMTB4RA1-S	480RGB*272	6(Gray Inversion)	105.5*67.2*4.0	95.04*53.856	Parallel RGB-24 bit / 40pin (B)		400	20~70/-30~80	0.768W	4-wire RTP		CP
13-043YMTB8IA1-S	480RGB*272	6(Gray Inversion)	116.04*74.85*4.9	95.04*53.856	Parallel RGB-24 bit / 40pin (B)		400	20~70/-30~80	0.768W	PCT_I2C	FT5306	CP
13-043YMTB00A2-S	480RGB*272	6(Gray Inversion)	105.5*67.2*2.9	95.04*53.856	Parallel RGB-24 bit / 40pin (B)		900	20~70/-30~80	0.768W	None	Anti-Reflection	PI / CP
13-043YMTB00A3-S	480RGB*272	Free of All	105.5*67.2*2.9	95.04*53.856	Parallel RGB-24 bit / 40pin (B)		700	20~70/-30~80	0.768W	None	Optical Film	PI / 4W / CP
13-043YMTB4RA3-S	480RGB*272	6(Gray Inversion)	105.5*67.2*4.1	95.04*53.856	Parallel RGB-24 bit / 40pin (B)		570	20~70/-30~80	0.768W	4-wire RTP		
13-043YMTB4RA7-S	480RGB*272	6(Gray Inversion)	105.5*67.2*4.0	95.04*53.856	Parallel RGB-24 bit / 40pin (B)		220	20~70/-30~80	0.768W	4-wire RTP		CP
13-043YMTB00GAB-S	480RGB*272	6(Gray Inversion)	105.5*67.2*2.9	95.04*53.856	Parallel RGB-24 bit / 40pin (B)		1400	20~70/-30~80	1.152W	None		
13-043YMTB4GAB-S	480RGB*272	6(Gray Inversion)	105.5*67.2*4.0	95.04*53.856	Parallel RGB-24 bit / 40pin (B)		1100	20~70/-30~80	1.152W	4-wire RTP		
13-043YMCB4RD1-C	480RGB*272	6(Gray Inversion)	105.5*67.2*4.7	95.04*53.856	18/16/12/9/8 bits (8080/6800) system		400	20~70/-30~80		4-wire RTP	MCU IC_SSD1963	
13-050WMTB00B0-S	800RGB*480	6(Gray Inversion)	118.4*77.45*3.0	108.0*64.8	Parallel RGB-24 bit / 40pin (B)		1000	20~70/-30~80	1.12W	None		PI / 4W
13-050WMTB4RB0-S	800RGB*480	6(Gray Inversion)	118.4*77.45*4.1	108.0*64.8	Parallel RGB-24 bit / 40pin (B)		800	20~70/-30~80	1.12W	4-wire RTP		
13-050WMTB8IA0-S	800RGB*480	6(Gray Inversion)	142.0*94.0*5.45	108.0*64.8	Parallel RGB-24 bit / 40pin (B)		850	20~70/-30~80	1.12W	PCT_I2C	FT5306	
13-050WMTB00B0-S	800RGB*480	6(Gray Inversion)	118.4*77.45*6.35	108.0*64.8	LVDS-8 bit / 30pin / LED Dr		1000	20~70/-30~80	TBD	None		PI / 4W
13-050WMTB00B1-S	800RGB*480	Free of All	118.4*77.45*3.0	108.0*64.8	Parallel RGB-24 bit / 40pin (B)		800	20~70/-30~80	1.12W	None	Optical Film	PI / 4W
13-050WMTB00B2-S	800RGB*480	6(Gray Inversion)	118.4*77.45*3.0	108.0*64.8	Parallel RGB-24 bit / 40pin (B)		1000	20~70/-30~80	1.12W	None	Anti-Reflection	PI
13-050WMTB00K2-S	800RGB*480	6(Gray Inversion)	120.8*76*3.10	108.0*64.8	Parallel RGB-24 bit / 40pin (B)		350	20~70/-30~80	0.732W			
13-050WMTB4GK2-S	800RGB*480	6(Gray Inversion)	120.8*76*4.2	108.0*64.8	Parallel RGB-24 bit / 40pin (B)		280	20~70/-30~80	0.732W	4-wire RTP		
13-050WMTB8IAK2-S	800RGB*480	6(Gray Inversion)	142.0*94.0*5.55	108.0*64.8	Parallel RGB-24 bit / 40pin (B)		280	20~70/-30~80	0.732W	PCT_I2C	FT5306	
13-050WMTB00K3-S	800RGB*480	6(Gray Inversion)	120.8*76*3.10	108.0*64.8	Parallel RGB-24 bit / 40pin (B)		500	20~70/-30~80	0.732W			
13-050WMTB4GK3-S	800RGB*480	6(Gray Inversion)	120.8*76*4.2	108.0*64.8	Parallel RGB-24 bit / 40pin (B)		400	20~70/-30~80	0.732W	4-wire RTP		
13-050WMTB8IAK3-S	800RGB*480	6(Gray Inversion)	142.0*94.0*5.55	108.0*64.8	Parallel RGB-24 bit / 40pin (B)		400	20~70/-30~80	0.732W	PCT_I2C	FT5306	
13-057QMTB00B0-S	320RGB*240	6(Gray Inversion)	144*104.6*12.8	115.2*86.4	Parallel RGB-18 bit / 33pin (C)		800	20~70/-30~80	1.86W	None		AR / OF
13-057QMTB4RB0-S	320RGB*240	6(Gray Inversion)	144*104.6*14.3	115.2*86.4	Parallel RGB-18 bit / 33pin (C)		640	20~70/-30~80	1.86W	4-wire RTP		OF / 5W
13-057QMTB8IA0-S	320RGB*240	6(Gray Inversion)	144*104.6*15.28	115.2*86.4	Parallel RGB-18 bit / 33pin (C)		700	20~70/-30~80	1.86W	PCT_I2C	FT5216	OF
13-057QMTB00B1-S	320RGB*240	6(Gray Inversion)	144*104.6*12.8	115.2*86.4	Parallel RGB-18 bit / 33pin (C)		1500	20~70/-30~80	1.86W	None		AR / OF
13-057QMTB4RB1-S	320RGB*240	6(Gray Inversion)	144*104.6*14.3	115.2*86.4	Parallel RGB-18 bit / 33pin (C)		1200	20~70/-30~80	1.86W	4-wire RTP		OF / 5W
13-057QMTB00C0-S	320RGB*240	6(Gray Inversion)	144*104.6*12.8	115.2*86.4	Parallel RGB-18 bit / 40pin / LED.Dr (D)		800	20~70/-30~80	1.86W	None		AR / OF
13-057QMTB4RC0-S	320RGB*240	6(Gray Inversion)	144*104.6*14.3	115.2*86.4	Parallel RGB-18 bit / 40pin / LED.Dr (D)		640	20~70/-30~80	1.86W	4-wire RTP		OF / 5W
13-057QMTB8IAQ0-S	320RGB*240	6(Gray Inversion)	144*104.6*15.28	115.2*86.4	Parallel RGB-18 bit / 40pin / LED.Dr (D)		700	20~70/-30~80	1.86W	PCT_I2C	FT5216	OF
13-057QMTB00C1-S	320RGB*240	6(Gray Inversion)	144*104.6*12.8	115.2*86.4	Parallel RGB-18 bit / 40pin / LED.Dr (D)		1500	20~70/-30~80	2.05W	None		AR / OF
13-057QMTB4RC1-S	320RGB*240	6(Gray Inversion)	144*104.6*14.3	115.2*86.4	Parallel RGB-18 bit / 40pin / LED.Dr (D)		1200	20~70/-30~80	2.05W	4-wire RTP		OF / 5W
13-057QMSB0GT0-S	320RGB*240	6(Gray Inversion)	124.7*100.0*6.0	115.2*86.4	Parallel RGB-24 bit / 33pin / LED Dr		500	20~70/-30~80		None		
13-057QMSB4GT0-S	320RGB*240	6(Gray Inversion)	124.7*100.0*7.5	115.2*86.4	Parallel RGB-24 bit / 33pin / LED Dr		450	20~70/-30~80		4-wire RTP		
13-057QMTB00G0-S	320RGB*240	12(Gray Inversion)	144*104.6*13.0	115.2*86.4	RGB 18bit interface/33pin		600	20~70/-30~80	1.4W	有下鐵		
13-057QMTB4G0-S	320RGB*240	12(Gray Inversion)	144*104.6*14.5	115.2*86.4	RGB 18bit interface/33pin		480	20~70/-30~80	1.4W	有下鐵		
13-057YMTB00B0-S	640RGB*480	6(Gray Inversion)	144*104.6*12.8	115.2*86.4	Parallel RGB-18 bit / 33pin (C)		600	20~70/-30~80	1.86W	None		AR / OF
13-057YMTB4RB0-S	640RGB*480	6(Gray Inversion)	144*104.6*14.3	115.2*86.4	Parallel RGB-18 bit / 33pin (C)		480	20~70/-30~80	1.86W	4-wire RTP		OF / 5W
13-057YMTB8IA0-S	640RGB*480	6(Gray Inversion)	144*104.6*15.28	115.2*86.4	Parallel RGB-18 bit / 33pin (C)		500	20~70/-30~80	1.12W	PCT_I2C	FT5216	OF
13-057YMTB00B1-S	640RGB*480	6(Gray Inversion)	144*104.6*12.8	115.2*86.4	Parallel RGB-18 bit / 33pin (C)		1200	20~70/-30~80	1.86W	None		AR / OF
13-057YMTB4RB1-S	640RGB*480	6(Gray Inversion)	144*104.6*14.3	115.2*86.4	Parallel RGB-18 bit / 33pin (C)		960	20~70/-30~80	1.86W	4-wire RTP		OF / 5W
13-057YMTB8IA1-S	640RGB*480	6(Gray Inversion)	144*104.6*15.28	115.2*86.4	Parallel RGB-18 bit / 33pin (C)		1000	20~70/-30~80	1.12W	PCT_I2C	FT5216	OF
13-057YMTB00C0-S	640RGB*480	6(Gray Inversion)	144*104.6*12.8	115.2*86.4	Parallel RGB-18 bit / 40pin / LED.Dr (D)		600	20~70/-30~80	1.86W	None		AR / OF
13-057YMTB4RC0-S	640RGB*480	6(Gray Inversion)	144*104.6*14.3	115.2*86.4	Parallel RGB-18 bit / 40pin / LED.Dr (D)		480	20~70/-30~80	1.86W	4-wire RTP		OF / 5W
13-057YMTB8IAQ0-S	640RGB*480	6(Gray Inversion)	144.0*104.6*15.28	115.2*86.4	Parallel RGB-18 bit / 40pin / LED.Dr (D)		500	20~70/-30~80		PCT_I2C	FT5216	
13-057YMTB00C1-S	640RGB*480	6(Gray Inversion)	144*104.6*12.8	115.2*86.4	Parallel RGB-18 bit / 40pin / LED.Dr (D)		1200	20~70/-30~80	2.05W	None		AR / OF
13-057YMTB4RC1-S	640RGB*480	6(Gray Inversion)	144.0*104.6*14.3	115.2*86.4	Parallel RGB-18 bit / 40pin / LED.Dr (D)		960	20~70/-30~80	2.05W	4-wire RTP		OF / 5W
13-057YMTB8IAQ1-S	640RGB*480	6(Gray Inversion)	144.0*104.6*15.28	115.2*86.4	Parallel RGB-18 bit / 40pin / LED.Dr (D)		1000	20~70/-30~80	2.25W	PCT_I2C	FT5216	
13-057YMTB00C2-S	640RGB*480	6(Gray Inversion)	144.0*104.6*15.28	115.2*86.4	Parallel RGB-18 bit / 40pin / LED.Dr (D)		1500	20~70/-30~80	2.25W			
13-057YMTB00G0-S	640RGB*480	6(Gray Inversion)	144*104.6*13.0	115.2*86.4	RGB 18bit interface/33pin		450	20~70/-30~80	1.39W	有下鐵		
13-057YMTB4G0-S	640RGB*480	6(Gray Inversion)	144*104.6*14.5	115.2*86.4	RGB 18bit interface/33pin		360	20~70/-30~80	1.39W	有下鐵		
13-057YMLB00B0-S	640RGB*480	6(Gray Inversion)	144*104.6*12.8	115.2*86.4	LVDS-6 bit / 20pin (E)		600	20~70/-30~80	1.12W	None		AR / OF
13-057YMLB4RB0-S	640RGB*480	6(Gray Inversion)	144*104.6*14.3	115.2*86.4	LVDS-6 bit / 20pin (E)		480	20~70/-30~80	1.12W	4-wire RTP		OF / 5W
13-057YMLB8IA0-S	640RGB*480	6(Gray Inversion)	144*104.6*15.28	115.2*86.4	LVDS-6 bit / 20pin (E)		500	20~70/-30~80	1.12W	PCT_I2C	FT5216	OF
13-057YMLB00B1-S	640RGB*480	6(Gray Inversion)	144*104.6*12.8	115.2*86.4	LVDS-6 bit / 20pin (E)		1200	20~70/-30~80	1.86W	None		AR / OF
13-057YMLB4RB1-S	640RGB*480	6(Gray Inversion)	144*104.6*14.3	115.2*86.4	LVDS-6 bit / 20pin (E)	</						

Model No.	Resolution	Viewing Direction	Outline Dimension	Active Area	Code : A.B.C.D.xxx means same interface	L (cd/m2)	Temperature O.T/ST	BL Power consumption	Touch Panel	Note	Options
13-057VMTB4RA1-S	640RGB*480	12(Gray inversion)	127*98.43*7.0	115.2*86.4	Parallel RGB-18 bit / 40pin / LED.Dr (F)		720	20~70/-30~80	1.7W	4-wire RTP	
13-057VMTB00A2-S	640RGB*480	Free of All	127**98.43**5.8	115.2*86.4	Parallel RGB-18 bit / 40pin / LED.Dr (F)		630	20~70/-30~80	1.7W	None	
13-070WMTB00A0-S	800RGB*480	6(Gray inversion)	165.0*104.0*3.5	153.6*86.64	Parallel RGB-18 bit / 40pin / LED.Dr (G)		650	20~70/-30~80	2.25W	None	AR / OF
13-070WMTB4RA0-S	800RGB*480	6(Gray inversion)	165.0*104.0*5.3	153.6*86.64	Parallel RGB-18 bit / 40pin / LED.Dr (G)		500	20~70/-30~80	2.25W	4-wire RTP	OF / SW
13-070WOTB00A0-S	800RGB*480	Free direction	165.0*104.0*4.2	153.6*86.64	Parallel RGB-18 bit / 40pin / LED.Dr (G)		520	20~70/-30~80	2.25W		
13-070WMTBIAA0-S	800RGB*480	6(Gray inversion)	165.0*104.0*9.08	153.6*86.64	Parallel RGB-18 bit / 40pin / LED.Dr (G)		580	20~70/-30~80	2.25W	PCT_I2C	FT5306
13-070WMTB00A1-S	800RGB*480	6(Gray inversion)	165.0*104.0*3.5	153.6*86.64	Parallel RGB-18 bit / 40pin / LED.Dr (G)		1000	20~70/-30~80	2.25W	None	AR / OF
13-070WMTB4RA1-S	800RGB*480	6(Gray inversion)	165.0*104.0*5.3	153.6*86.64	Parallel RGB-18 bit / 40pin / LED.Dr (G)		800	20~70/-30~80	2.25W	4-wire RTP	OF / SW
13-070WMTBIAA1-S	800RGB*480	6(Gray inversion)	165.0*104.0*9.08	153.6*86.64	Parallel RGB-18 bit / 40pin / LED.Dr (G)		850	20~70/-30~80	2.25W	PCT_I2C	FT5306
13-070WMTB00A2-S	800RGB*480	6(Gray inversion)	165.0*104.0*3.5	153.6*86.64	Parallel RGB-18 bit / 40pin / LED.Dr (G)		400	20~70/-30~80	2.25W	None	
13-070WMTB4RA2-S	800RGB*480	6(Gray inversion)	165.0*104.0*5.3	153.6*86.64	Parallel RGB-18 bit / 40pin / LED.Dr (G)		320	20~70/-30~80	2.25W	4-wire RTP	
13-070WMTBIAA2-S	800RGB*480	6(Gray Inversion)	165.0*104.0*9.08	153.6*86.64	Parallel RGB-18 bit / 40pin / LED.Dr (G)		360	20~70/-30~80	2.25W	PCT_I2C	FT5306
13-070WMTB00B0-S	800RGB*480	6(Gray inversion)	165.0*104.0*5.5	153.6*86.64	Parallel RGB-18 bit / 40pin		1800	20~70/-30~80	5.376W		
13-070WMTB00B1-S	800RGB*480	6(Gray inversion)	165.0*104.0*5.5	153.6*86.64	Parallel RGB-18 bit / 40pin		2500	20~70/-30~80	5.376W		
13-070WMTB00C0-S	800RGB*480	6(Gray inversion)	165.0*104.44*5.3	152.4*91.44	Parallel RGB-18 bit / 40pin (H)		350	20~70/-30~80	1.58W	None	SW
13-070WMTB4RC0-S	800RGB*480	6(Gray inversion)	165.0*104.44*6.9	152.4*91.44	Parallel RGB-18 bit / 40pin (H)		280	20~70/-30~80	1.58W	4-wire RTP	
13-070WMLB0CG0-S	800RGB*480	6(Gray inversion)	165.0*104.44*5.3	152.4*91.44	LVDS 6bit / LED Dr		350	20~70/-30~80		None	
13-070WMLB4CG0-S	800RGB*480	6(Gray inversion)	165.0*104.44*6.9	152.4*91.44	LVDS 6bit / LED Dr		280	20~70/-30~80		4-wire RTP	
13-070WMLB00A0-S	800RGB*480	6(Gray Inversion)	165.0*104.0*3.5	153.6*86.64	LVDS-6 bit / 20pin / LED Dr (I)		650	20~70/-30~80	2.25W	None	AR / OF
13-070WMLB4RA0-S	800RGB*480	6(Gray inversion)	165.0*104.0*5.3	153.6*86.64	LVDS-6 bit / 20pin / LED Dr (I)		500	20~70/-30~80	2.25W	4-wire RTP	OF / SW
13-070WMLBIAA0-S	800RGB*480	6(Gray Inversion)	165.0*104.0*5.98	153.6*86.64	LVDS-6 bit / 20pin / LED Dr (I)		580	20~70/-30~80	2.25W	PCT_I2C	FT5306
13-070WMLB00A1-S	800RGB*480	6(Gray Inversion)	165.0*104.0*3.5	153.6*86.64	LVDS-6 bit / 20pin / LED Dr (I)		1000	20~70/-30~80	2.25W	None	AR / OF
13-070WMLB4RA1-S	800RGB*480	6(Gray inversion)	165.0*104.0*5.3	153.6*86.64	LVDS-6 bit / 20pin / LED Dr (I)		800	20~70/-30~80	2.25W	4-wire RTP	OF / SW
13-070WMLBIAA1-S	800RGB*480	6(Gray Inversion)	165.0*104.0*5.98	153.6*86.64	LVDS-6 bit / 20pin / LED Dr (I)		850	20~70/-30~80	2.25W	PCT_I2C	FT5306
13-070WMLBIBAA1-S	800RGB*480	6(Gray Inversion)	165.0*104.0*5.98	153.6*86.64	LVDS-6 bit / 20pin / LED Dr (I)		850	20~70/-30~80	2.25W	PCT_I2C	
13-070WMLB00A2-S	800RGB*480	6(Gray Inversion)	165.0*104.0*3.5	153.6*86.64	LVDS-6 bit / 20pin / LED Dr (I)		400	20~70/-30~80	2.25W	None	
13-070WMLB4RA2-S	800RGB*480	6(Gray inversion)	165.0*104.0*5.3	153.6*86.64	LVDS-6 bit / 20pin / LED Dr (I)		320	20~70/-30~80	2.25W	4-wire RTP	
13-070WMLB00B1-S	800RGB*480	6(Gray inversion)	165.0*104.0*5.05	153.6*86.64	LVDS-6 bit / 20pin / LED Dr (I)		2500	20~70/-30~80	5.376W		
13-070WMLBLCAB1-S	800RGB*480	6(Gray Inversion)	165.0*104.0*10.68	153.6*86.64	LVDS-6 bit / 20pin / LED Dr (I)		2000	20~70/-30~80	5.376W	PCT I2C/USB	ILI2511
13-070XILB0GH1-S	1024RGB*600	IPS	164.9*100.0*4.6	154.21*85.92	LVDS-6 bit / 20pin / LED Dr		700	20~70/-30~70	2.15W	None	
13-070XILB4GH1-S	1024RGB*600	IPS	164.9*100.0*5.10	154.21*85.92	LVDS-6 bit / 20pin / LED Dr		560	20~70/-30~70	2.15W	4-wire RTP	
13-070XILBIAH1-S	1024RGB*600	IPS	164.9*100.0*5.20	154.21*85.92	LVDS-6 bit / 20pin / LED Dr		600	20~70/-30~70	2.15W	PCT_I2C	FT5306
13-070XILB0GH6-S	1024RGB*600	IPS	164.9*100.0*5.05	154.21*85.92	LVDS-6 bit / 20pin		1500	20~70/-30~70	5.376W	None	
13-070XIEBCAH6-S	1024RGB*600	IPS	165.0*104.0*7.53	154.21*85.92	LVDS-8 bit / 20pin		1300	20~70/-30~70	5.376W		
13-080WMSC0GA0	800RGB*480	6(Gray inversion)	192.8**116.9* 6.4	176.64* 99.36	Parallel RGB-24 bit / 50pin		450	20~70/-30~80		None	
13-080WMSC4GA0	800RGB*480	6(Gray inversion)	192.8**116.9*7.92	176.64* 99.36	Parallel RGB-24 bit / 50pin		360	20~70/-30~80		4-wire RTP	
13-080WMSBIA0-S	800RGB*480	6(Gray inversion)	210.0*134.0* 8.83	176.64* 99.36	Parallel RGB-24 bit / 50pin		400	20~70/-30~80		PCT_I2C	FT5406
13-0805MTB00A0-S	800RGB*600	6(Gray Inversion)	183.0*141.0*5.8	162.0*121.5	Parallel RGB-18 bit / 40pin (J)		500	20~70/-30~80	1.782W	None	
13-0805MTBIAA0-S	800RGB*600	6(Gray Inversion)	183.0*141.0*8.50	162.0*121.50	Parallel RGB-18 bit / 40pin (J)		420	20~70/-30~80	3.25W	PCT_I2C	FT5826
13-0805MTB4RB0-S	800RGB*600	6(Gray Inversion)	183.0*141.0*7.35	162.0*121.5	Parallel RGB-18 bit / 40pin (J)		400	20~70/-30~80	1.782W	4-wire RTP	RTP TOP SIDE
13-0805MTB00A1-S	800RGB*600	6(Gray Inversion)	183.0*141.0*5.8	162.0*121.5	Parallel RGB-18 bit / 40pin / LED.Dr (G)		500	20~70/-30~80	2.25W	None	PI / 4W / SW
13-0805MTB00A2-S	800RGB*600	6(Gray Inversion)	183.0*141.0*5.8	162.0*121.5	Parallel RGB-18 bit / 40pin (J)		750	20~70/-30~80	2.78W	None	PI / 4W / SW
13-0805MTB00A3-S	800RGB*600	6(Gray Inversion)	183.0*141.0*6.3	162.0*121.5	Parallel RGB-18 bit / 40pin (J)		1300	20~70/-30~80	2.35W*2	None	PI / 4W / SW / LD
13-0805MTBIAA3-S	800RGB*600	6(Gray Inversion)	183.0*141.0*9.00	162.0*121.50	Parallel RGB-18 bit / 40pin (J)		1200	20~70/-30~80	2.325W	PCT_I2C	FT5826
13-0805MLB00A0-S	800RGB*600	6(Gray Inversion)	183.0*141.0*5.8	162.0*121.5	LVDS-6 bit / 20pin (K)		500	20~70/-30~80	1.782W	None	
13-0805MLB00A1-S	800RGB*600	6(Gray Inversion)	183.0*141.0*5.8	162.0*121.5	LVDS-6 bit / 20pin (K)		750	20~70/-30~80	2.78W	None	PI / 4W / SW
13-0805MLB4RB0-S	800RGB*600	6(Gray Inversion)	183.0*141.0*7.35	162.0*121.5	LVDS-6 bit / 20pin (K)		400	20~70/-30~80	1.782W	4-wire RTP	RTP TOP SIDE
13-0805MLB4RB5-S	800RGB*600	6(Gray Inversion)	183.0*141.0*7.3	162.0*121.50	LVDS-6 bit / 20pin (K)		250	20~70/-30~80	1.782W	4-wire RTP	RTP TOP SIDE
13-080GLB00A0-S	1024RGB*768	IPS	183.0*141.0*6.3	162.05*121.54	LVDS 6bit/20pin		1200	10~50/-20~60	2.6W*2	None	two BL Cable
13-080GLB4RB0-S	1024RGB*768	IPS	183.0*141.0*8.75	162.05*121.54	LVDS-6 bit / 20pin (K)		1000	10~50/-20~60	2.6W*2	4-wire RTP	two BL Cable
13-080GLB5GA0-S	1024RBG*768	IPS	183.0*141.0*11.05	162.05*121.54	LVDS 6bit/20pin		1000	10~50/-20~60	2.6W*2		
13-080GLB00A1-S	1024RGB*768	IPS	183.0*141.0*6.3	162.05*121.54	LVDS-6 bit / 20pin / LED Dr (I)		600	10~50/-20~60	3.1W	None	PI / 5W / LD / 8b
13-080GLB4BAH1-S	1024RGB*768	IPS	183.0*141.0*7.85	162.05*121.54	LVDS-6 bit / 20pin / LED Dr (I)		500	10~50/-20~60	3.1W	4-wire RTP	LD / 8b
13-080GLB5GA1-S	1024RGB*768	IPS	183.0*141.0*12.25	162.05*121.54	lvds 6bit/20pin/LED Dr		480	10~50/-20~60	3.25W	5-wire RTP	
13-080GLBUAA2-S	1024RGB*768	IPS	183.0*141.0*8.995	162.05*121.54	LVDS 6/8 bit interface/40pins		500	10~50/-20~60	2.64W	PCT USB	FT5826
13-080GIEB0QA0-S	1024RGB*768	IPS	183.0*141.0*9.60	162.05*121.54	LVDS 6/8 bit interface/30pins		1200	10~50/-20~60	2.64W	None	two BL Cable
13-080IEB0HA0-S	1600RGB*480	IPS	208*73**5.4	194.4*58.32	LVDS 8bit interface		500	20~70/-30~80	1.98W	None	
13-080IEB0HA1-S	1600RGB*480	IPS	208*73**5.4	194.4*58.32	LVDS 8bit interface		2000	20~70/-30~80	5.6W	None	
13-080IEB0HB0-S	1600RGB*480	IPS	208.0*73.0*6.5	194.4*58.32	LVDS 8bit interface/LED Dr		500	20~70/-30~80			
13-080IEB0HB1-S	1600RGB*480	IPS	208.0*73.0*6.5	194.4*58.32	LVDS 8bit interface/LED Dr		2000	20~70/-30~80			
13-101XILB0GA0-S	1024RGB*600	IPS	234.9*143.0*4.6	222.72*125.28	LVDS-6 bit / 20pin /LED Dr		600	20~70/-30~80			
13-101XIEB0GA0-S	1024RGB*600	IPS	234.9*143.0*4.6	222.72*125.28	LVDS-8 bit / 30pin /LED Dr		600	20~70/-30~80			
13-1012IEB0HH0-S	1280RGB*800	IPS	229.46*149.1*7.38	216.96*135.6	LVDS-8 bit / 30pin / LED Dr		600	20~70/-30~80		TBD	replace 00C0-S
13-1012IEB4UH0-S	1280RGB*800	IPS	229.46*149.1*6.50	216.96*135.6	LVDS-8 bit / 30pin / LED Dr		400	20~70/-30~80		TBD	
13-1012IEBIAH0-S	1280RGB*800	IPS	229.46*149.1*7.38	216.96*135.6	LVDS-8 bit / 30pin / LED Dr		450	20~70/-30~80		TBD	FT5826
13-1012IEBUAH0-S	1280RGB*800	IPS	229.46*149.1*7.38	216.96*135.6	LVDS-8 bit / 30pin / LED Dr		450	20~70/-30~80		TBD	FT5826
13-1012IEBCAH0-S	1280RGB*800	IPS	245.96*164.6*7.38	216.96*135.6	LVDS-8 bit / 30pin / LED Dr		500	20~70/-30~80		TBD	PCT_USB/I2C
13-1012IEBCBH0-S	1280RGB*800	IPS	245.96*149.1*7.38	216.96*135.6	LVDS-8 bit / 30pin / LED Dr		500	20~70/-30~80		TBD	PCT_USB/I2C
13-1012IEB0HH1-S	1280RGB*800	IPS	229.46*149.1*4.80</								

Model No.	Resolution	Viewing Direction	Outline Dimension	Active Area	Code : A.B.C.D.xxx means same interface	L (cd/m2)	Temperature 0,T/5,T	BL Power consumption	Touch Panel	Note	Options
13-1045MLB0001-S	800RGB*600	6(Gray inversion)	236*176.9*5.6	211.2*158.4	LVDS-6 bit / 20pin/LED Dr	450	20~70°/30~80				
13-1045MLB4GDI-S	800RGB*600	6(Gray inversion)	236*176.9*7.1	211.2*158.4	LVDS-6 bit / 20pin/LED Dr	350	20~70°/30~80				
13-1045MLB00C1-S	800RGB*600	6(Gray inversion)	243*184*6.5	211.2*158.4	LVDS-6/8 bit / 20pin (Q)	1200	30~80°/30~80	7.3W	None		4W / 5W / PU
13-1046VEB0GA0-S	1024RGB*768	MVA	225.5*176.3*8.4	210.432*157.824	LVDS-6 or 8 bit / 30pin	1000	30~70°/30~80				
13-1046GLB00A0-S	1024RGB*768	6(Gray inversion)	236*174*5.7	211.2*158.4	LVDS-6 bit / 30pin (M)	1000	20~70°/30~80	4.8W	None		LD
13-1046GLB4RA0-S	1024RGB*768	6(Gray inversion)	236*174*7.25	211.2*158.4	LVDS-6 bit / 30pin (M)	800	20~70°/30~80	4.8W	4-wire RTP		LD
13-1046GLB5RA0-S	1024RGB*768	6(Gray inversion)	236*174*8.0	211.2*158.4	LVDS-6 bit / 30pin (M)	800	20~70°/30~80	4.8W	5-wire RTP		LD
13-1046GLB1AA0-S	1024RGB*768	6(Gray inversion)	236*174.3*8.85	211.2*158.4	LVDS-6 bit / 30pin (M)	900	20~70°/30~80	2.5W	PCT_12C	FT5606	
13-1046GLBCA0A-S	1024RGB*768	6(Gray inversion)	264.6*204.0*8.22	211.2*158.4	LVDS-6 bit / 30pin (M)	900	20~70°/30~80	4.8W			
13-1046GLB00A0-S	1024RGB*768	Free of All	236*174.3*5.7	211.2*158.4	LVDS-6 bit / 30pin (M)	800	20~70°/30~80	4.8W	None		PI / PU / LD / 4W / 5W
13-1046GLB00A1-S	1024RGB*768	6(Gray inversion)	236*174*5.7	211.2*158.4	LVDS-6 bit / 30pin (M)	400	20~70°/30~80	2.5W	None		
13-1046GLB4RA1-S	1024RGB*768	6(Gray inversion)	236*174*7.25	211.2*158.4	LVDS-6 bit / 30pin (M)	320	20~70°/30~80	2.5W	4-wire RTP		
13-1046GLB5RA1-S	1024RGB*768	6(Gray inversion)	236*174*8.0	211.2*158.4	LVDS-6 bit / 30pin (M)	320	20~70°/30~80	2.5W	5-wire RTP		
13-1046GLB1AA1-S	1024RGB*768	6(Gray inversion)	236*174.3*8.85	211.2*158.4	LVDS-6 bit / 30pin (M)	360	20~70°/30~80	2.5W	PCT_12C	FT5606	
13-1046GLB00B0-S	1024RGB*768	6(Gray inversion)	236*174.3*5.7	211.2*158.4	LVDS-6 bit / 30pin (M)	1200	20~70°/30~80	6.4W	None		LD
13-1046GLB4RB0-S	1024RGB*768	6(Gray inversion)	236*174.3*7.25	211.2*158.4	LVDS-6 bit / 30pin (M)	960	20~70°/30~80	6.4W	4-wire RTP		LD
13-1046GLB00B1-S	1024RGB*768	6(Gray inversion)	236*174.3*5.7	211.2*158.4	LVDS-6 bit / 30pin (M)	1500	20~70°/30~80	6.4W	None		LD
13-1215MLB00A0-S	800RGB*600	6(Gray inversion)	276.0*209.0*9.1	246.0*184.50	LVDS-6 bit /20pin/LED Dr.	450	20~70°/30~80		None		
13-1215MLB4GA0-S	800RGB*600	6(Gray inversion)	276.0*209.0*11.45	246.0*184.50	LVDS-6 bit /20pin/LED Dr.	360	20~70°/30~80		4-wire RTP		
13-1216GLB00A0-S	1024RGB*768	Wide viewing angle	260.5*204*7.2	245.76*184.32	LVDS-8 bits / 20pin + LED Dr (O)	500	30~70°/40~80	4.8W	None		
13-1216GLB4GA0-S	1024RGB*768	Wide viewing angle	260.5*204*9.55	245.76*184.32	LVDS-8 bits / 20pin + LED Dr (O)	400	20~70°/30~80	4.8W	4-wire RTP		
13-1216MLBPSA0-S	1024RGB*768	Wide viewing angle	280.67*226.2*10.5	245.76*184.32	LVDS 6/8BIT/20pin	450	20~70°/30~80	4.8W	PCT_USB		
13-1216GLBUBA0-S	1024RGB*768	Wide viewing angle	290.0*5220.5*10.2	245.76*184.32	LVDS 6/8BIT/20pin	450	20~70°/30~80	4.8W	PCT_USB	WDT8753T	
13-1216GLC00B0-S	1024RGB*768	Wide viewing angle	279*209*9.0	245.76*184.32	LVDS 6/8 bits / 20pin	1000	30~85°/30~85	6.765W	None		4W / PI / PU
13-1216GLC4GB0-S	1024RGB*768	Wide viewing angle	279*209.0*11.11	245.76*184.32	LVDS 6/8 bits / 20pin	800	20~70°/30~80	6.765W			
13-1216GLCPSB0-S	1024RGB*768	Wide viewing angle	287.67*226.2*12.08	245.76*184.32	LVDS 6/8 bits / 20pin	850	20~70°/30~80	12.81W	PCT USB	EXC7200	
13-1216GLC00B1-S	1024RGB*768	Wide viewing angle	279*209*9.0	245.76*184.32	LVDS 6/8 bits / 20pin	1500	30~85°/30~85	12.81W	None		4W / PI / PU
13-1216MLCPSB1-S	1024RGB*768	Wide viewing angle	287.67*226.2*12.08	245.76*184.32	LVDS 6/8 bits / 20pin	1300	20~70°/30~80	12.81W	PCT USB	EXC7200	
13-1212VLB00A0-S	1280RGB*800	MVA	278*184*8.16	261.12*163.2	LVDS-8 bits / 30pin / LED Dr (N)	400	10~70°/20~80	8.4W	None		
13-1212VLB4RA0-S	1280RGB*800	MVA	278*184*10.38	261.12*163.2	LVDS-8 bits / 30pin / LED Dr (N)	320	10~70°/20~80	8.4W	4-wire RTP		
13-1212VLB5RA0-S	1280RGB*800	MVA	278*184*10.38	261.12*163.2	LVDS-8 bits / 30pin / LED Dr (N)	320	10~70°/20~80	8.4W	5-wire RTP		
13-1212VLB00A1-S	1280RGB*800	MVA	278*184*8.16	261.12*163.2	LVDS 6/8 bits / 20pin	1000	10~70°/20~80	9.54W		G12111-101	
13-1212VLB00A2-S	1280RGB*800	MVA	278*184*8.16	261.12*163.2	LVDS 6/8 bits / 20pin	1500	10~70°/20~80	14.322W			
13-1212MLB0GB0-S	1280RGB*800	12(Gray inversion)	278*184*8.6	261.12*163.2	LVDS 6/8 bits / 20pin	1200	30~80°/30~80	8.4W		Sharp TN	
13-1212VLBUBA0-S	1280RGB*800	IPS	298.24*200.32*12.9	261.12*163.2	LVDS 88bit/30pin	380	20~70°/30~80		EE31462938CABC-A001		
13-1506MEA0A01-S	1024RGB*768	6(Gray inversion)	326.5*253.5*12	304.13*228.1	LVDS 6/8bit/20pins	1600	30~85°/30~85	15.84W			
13-1506MEA5A1-S	1024RGB*768	6(Gray inversion)	326.5*253.5*14.5	304.13*228.1	LVDS 6/8bit/20pins	1250	10~60°/20~70	15.8W			
13-1506MEA0A01-S	1024RGB*768	6(Gray inversion)	346.0*270.0*14.73	304.13*228.1	LVDS 6/8bit/20pins	1350	20~70°/30~80	15.84W		EETI controller	
13-1562MLAAAG1-S	1366RGB*768	6(Gray inversion)	363.8*215.9*16.85	344.23*193.54	LVDS 6/8bit/20pins	1000	0°60°/20~60	11.95W			
13-1907MEE00A0-S	1280 (H) x RGB x 102	Wide view direction	396.0*324.0*17.8	376.32*301.06	Dual Channel LVDS 8 bit/30pin	1500	0°50°/20~60	19.56W			
Options Explanation : AR(Anti-Reflection pol) / OF(Optical Film) / 4W(4W RTP) / 5W(5W RTP) / PI(PCT 12C) / PU(PCT USB) / L(6bits LVDS PCB)/E (8 bits LVDS PCB) / LD(LED Driver Board) / CP(CPU PCB)											