



XBEE® ZIGBEE MESH KIT

Provides a hands-on way to learn how to use XBee RF modules for device connectivity and mesh networking

Digi's XBee ZigBee Mesh Kit offers a great way to learn how to use XBee RF modules for device connectivity and ZigBee-based mesh networking. Starting with simple examples, we provide step-by-step guidance as you assemble the kit components to create reliable, low-power device communications and sensor networks.

Mesh networking is a powerful way to route data. Range is extended by allowing data to hop from node to node, and reliability is increased by "self-healing," the ability to create alternate paths when one node fails or a connection is lost. ZigBee is one of the most popular mesh networking protocols, specifically designed for low-data rate and low-power applications. ZigBee is an open standard, enabling interoperability between different device manufacturers.

This kit is designed for anyone interested in getting started in the world of ZigBee. Hardware and software engineers, corporate technologists, or educators and students can quickly learn more about ZigBee technology through hands-on examples in the kit, utilizing XBee ZigBee modules.

XBee ZigBee Modules Included in the Kit

XBee and XBee-PRO® ZigBee modules are ideal for applications in the energy and controls markets where time-to-market and reliability are critical. With Digi's extensive and easy-to-use XBee API framework, customers can get their ZigBee product to market faster than any other module available in the

The Kit Includes:

- ✓ 3 XBee Grove Development Board
- ✓ 3 XBee ZigBee Modules
- ✓ 3 Micro-USB Cables
- ✓ 2 XBee Stickers

NUMBER	DESCRIPTION
XKB2-Z7T-WZM	XBee ZigBee Mesh Kit
XKB2-Z7T-ZM	XBee-PRO ZigBee Mesh Kit

industry. Features like binding and multicasting also allow for simple integration for Home Automation applications.

Our modules are available in the popular XBee through-hole and surface mount form factors, providing customers the flexibility to substitute one XBee technology for another with minimal development time and risk. Using the long range XBee-PRO variant, customers can get up to two miles (3200 meters) LoS range.



SPECIFICATIONS

XBee® ZigBee

Standard

| Programmable

XBee-PRO® ZigBee

Standard

| Programmable

PERFORMANCE

DATA RATE	RF 250 Kbps, Serial up to 1 Mbps		
INDOOR/URBAN RANGE	200 ft (60 m)		300 ft (90 m)
OUTDOOR/RF LINE-OF-SIGHT RANGE	4000 ft (1200 m)		2 miles (3200 m)
TRANSMIT POWER	3.1 mW (+5 dBm) / 6.3 mW(+8 dBm) boost mode		63 mW (+18 dBm)
RECEIVER SENSITIVITY (1% PER)	-100 dBm / -102 dBm boost mode		-101 dBm

FEATURES

SERIAL DATA INTERFACE	UART, SPI		
CONFIGURATION METHOD	API or AT commands, local or over-the-air		
FREQUENCY BAND	ISM 2.4 GHz		
FORM FACTOR	Through-Hole, Surface Mount		
INTERFERENCE IMMUNITY	DSSS (Direct Sequence Spread Spectrum)		
ADC INPUTS	(4) 10-bit ADC inputs		
DIGITAL I/O	15		
ANTENNA OPTIONS	Through-Hole: PCB Antenna, U.FL Connector, RPSMA Connector, or Integrated Wire SMT: RF Pad, PCB Antenna, or U.FL Connector		
OPERATING TEMPERATURE	-40° C to +85° C		
DIMENSIONS (L X W X H) AND WEIGHT	Through-Hole: 0.960 x 1.087 in (2.438 x 2.761 cm) SMT: 0.866 x 1.33 x 0.120 in (2.199 x 3.4 x 0.305 cm)		Through-Hole: 0.960 x 1.297 in (2.438 x 3.294 cm) SMT: 0.866 x 1.33 x 0.120 in (2.199 x 3.4 x 0.305 cm)

PROGRAMMABILITY

MEMORY	N/A	32 KB Flash / 2 KB RAM	N/A	32 KB Flash / 2 KB RAM
CPU/CLOCK SPEED	N/A	HCS08 / up to 50.33 MHz	N/A	HCS08 / up to 50.33 MHz

NETWORKING AND SECURITY

PROTOCOL	ZigBee PRO 2007, HA-Ready with support for binding/multicasting		
ENCRYPTION	128-bit AES		
RELIABLE PACKET DELIVERY	Retries/Acknowledgements		
IDS	PAN ID and addresses, cluster IDs and endpoints (optional)		
CHANNELS	16 channels		15 channels

POWER REQUIREMENTS

SUPPLY VOLTAGE	2.1 to 3.6V		2.7 to 3.6V	
TRANSMIT CURRENT	33 mA @ 3.3 VDC / 45 mA boost mode	47 mA @ 3.3 VDC / 59 mA boost mode	120 mA @ 3.3 VDC	120 mA @ 3.3 VDC
RECEIVE CURRENT	28 mA @ 3.3 VDC / 31 mA boost mode	42 mA @ 3.3 VDC / 45 mA boost mode	31 mA @ 3.3 VDC	45 mA @ 3.3 VDC
POWER-DOWN CURRENT	<1 uA @ 25° C	1.5 uA @ 25° C	<1 uA @ 25° C	1.5 uA @ 25° C

REGULATORY APPROVALS

FCC, IC (NORTH AMERICA)	Yes	Yes
ETSI (EUROPE)	Yes	No
C-TICK (AUSTRALIA)	Yes	Yes
TELEC (JAPAN)	Yes	No

It's the easy and fast way to build a wireless mesh network using Digi's XBee modules. To learn more visit docs.digi.com.



877-912-3444 | 952-912-3444