

PRODUCT SPECIFICATIONS

For Customer: _____

☐ : APPROVAL FOR SPECIFICATION

Customer Model No. _____

☐ : APPROVAL FOR SAMPLE

 Module No.: ZW-T043QPS-10CP
Date : 2018-11-30

Table of Contents

No.	Item	Page
1	Cover Sheet(Table of Contents)	
2	Revision Record	
3	General Specifications	
4	Outline Drawing	
5	Absolute Maximum Ratings	
6	Electrical Specifications	
7	Optical Characteristics	
8	Reliability Test Items and Criteria	
9	Precautions for Use of LCD Modules	

For Customer's Acceptance:

Approved By	Comment

PREPARED	CHECKED	VERIFIED BY QA DEPT	VERIFIED BY R&D DEPT
GZH	John		Dmjiaing

2. Revision Record

[illegible]

3. General Specifications

ZW-T043QPS-10CP is a TFT-LCD module. It is composed of a TFT-LCD panel, driver IC, FPC, a back light and CTP unit. The 4.3" display area contains 480 x 272 pixels and can display up to 16.7M colors. This product accords with RoHS environmental criterion.


3.1 LCD parameter

Item	Contents	Unit	Note
LCD Type	TFT	-	
Display color	16.7M		
Viewing Direction	12	O'Clock	
Operating temperature	-20~+70	°C	
Storage temperature	-30~+80	°C	
Module size	Refer to outline drawing	mm	
Active Area(W×H)	95.04X53.86	mm	
Number of Dots	480×272	dots	
Controller	ST7282	-	
Power Supply Voltage	3.3	V	
Outline Dimensions	Refer to outline drawing	-	
Backlight	5*2-LEDs (white)	pcs	
Weight	---	g	
Interface	RGB888	-	

3.2 CTP parameter

Item	Contents	Unit	Note
Outline Size	104.84(H)X66.8(V)X1.45(T)	mm	
Cover View Area	97.04(H)X55.85(V)	mm	
CTP Resolution	480×272	-	
Interface Mode	IIC	-	
Touch Mode	5 Human fingers multi touch		
Controller	FT5436	-	
IIC Address	0x70	-	
Optical Characteristics	Transparency>=86%	-	
Surface Hardness	>=6H	-	

4.Outline.Drawing



5. Absolute Maximum Ratings($T_a=25^{\circ}\text{C}$)

5.1 Electrical Absolute Maximum Ratings.($V_{SS}=0\text{V}$, $T_a=25^{\circ}\text{C}$)

Item	Symbol	Min.	Max.	Unit	Note
Power Supply Voltage	V_{DD}	-0.3	3.6	V	1, 2

Notes:

1. If the module is above these absolute maximum ratings. It may become permanently damaged. Using the module within the following electrical characteristic conditions are also exceeded, the module will malfunction and cause poor reliability.
2. $V_{DD} > V_{SS}$ must be maintained.
3. Please be sure users are grounded when handing LCD Module.

5.2 Environmental Absolute Maximum Ratings.

Item	Storage		Operating		Note
	MIN.	MAX.	MIN.	MAX.	
Ambient Temperature	-30°C	80°C	-20°C	70°C	1,2
Humidity	-	-	-	-	3

1. The response time will become lower when operated at low temperature.
2. Background color changes slightly depending on ambient temperature.
The phenomenon is reversible.
3. $T_a \leq 40^{\circ}\text{C}$: 85%RH MAX.
 $T_a > 40^{\circ}\text{C}$: Absolute humidity must be lower than the humidity of 85%RH at 40°C .

6. Electrical Specifications and Instruction Code

6.1.1 LCM Electrical characteristics($V_{ss}=0V$, $T_a=25^{\circ}C$)

Parameter		Symbol	Condition	Min	Typ	Max	Unit	Note
Power supply		VDD	$T_a=25^{\circ}C$	3.0	3.3	3.6	V	
Input voltage	'H'	V_{IH}	$V_{DD}=3.3V$	$0.8V_{DD}$	-	V_{DD}	V	
	'L'	V_{IL}	$V_{DD}=3.3V$	0	-	$0.2V_{DD}$	V	

Note: 1: Tested in 1×1 chessboard pattern.

6.1.2 CTP Characteristics


Parameter		Symbol	MIN	TYP	MAX	Unit	Remark
Supply Voltage		VDD_CTP	2.8	-	3.6	V	
Input Signal Voltage	Low Level	V_{IL}	-0.3	-	$0.3 * V_{DD_CTP}$	V	
	High Level	V_{IH}	$0.7 * V_{DD_CTP}$	-	V_{DD_CTP}	V	
Output Signal Voltage	Low Level	V_{OL}	-	-	$0.3 * V_{DD_CTP}$	V	
	High Level	V_{OH}	$0.7 * V_{DD_CTP}$	-	-	V	

6.2 LED backlight specification(VSS=0V ,Ta=25°C)

Item	Symbol	Condition	Min	Typ	Max	Unit	Note
Supply voltage	V_f	$I_f=2*20mA$	-	15	-	V	
Uniformity	ΔBp	$I_f=2*20mA$	75	-	-	%	

Note:

LED power consumption is around 0.06W.



ILED VS TEMP

6.3 Interface signals

Pin No.	Symbol	I/O	Function
1	VLED-	P	LED back light(Cathode)
2	VLED+	P	LED back light(Anode)
3	GND	P	Ground.
4	VDD	P	Power supply
5-12	R0~R7	I	Red data bus
13-20	G0~G7	I	Green data bus
21-28	B0~B7	I	Blue data bus
29	GND	P	Ground.
30	PCLK	I	Data clock
31	DISP	I	Standby mode select pin
32	HSYNC	I	Line sync signal
33	VSYNC	I	Frame sync signal
34	DE	I	Data enable pin
35	NC	-	No connection.
36	GND	P	Ground.
37	XR	O	Touch panel
38	YD	O	
39	XL	O	
40	YU	O	

CTP PIN:

Pin No.	Symbol	I/O	Function
1	VDD	P	CTP power supply
2	GND	P	CTP Ground.
3	SCL	I	CTP serial clock signal
4	SDA	I	CTP serial Input/output data bus
5	INT	I	external Interrupt to the IC of CTP
6	WAKE	I	CTP reset


6.4 AC Characteristics

6.4.1 Parallel 24-bit RGB Timing Table

Item	Symbol	Min.	Typ.	Max.	Unit	Remark
DCLK Frequency	Fclk	8	9	12	MHz	
DCLK Period	Tclk	83	111	125	ns	
HSYNC	Period Time	Th	485	531	DCLK	
	Display Period	Thdisp		480	DCLK	
	Back Porch	Thbp	3	43	DCLK	By H_Blanking setting
	Front Porch	Thfp	2	8	DCLK	
	Pulse Width	Thw	2	4	DCLK	
VSYNC	Period Time	Tv	276	292	H	
	Display Period	Tvdisp		272	H	
	Back Porch	Tvbp	2	12	H	By V_Blanking setting
	Front Porch	Tvfp	2	8	H	
	Pulse Width	Tvw	2	4	H	

Note: It is necessary to keep Tvbp =12 and Thbp =43 in sync mode. DE mode is unnecessary to keep it.

6.4.2 SYNC-DE Mode Timing Diagram



7. Optical Characteristics

Item	Symbol		Condition	Min.	Typ.	Max.	Unit	Note
Brightness	Bp		$\theta=0^{\circ}$ $\Phi=0^{\circ}$	-	420	-	Cd/m ²	1
Uniformity	△Bp			75	-	-	%	1,2
Viewing Angle	3:00		Cr≥10	-	65	-	Deg	3
	6:00			-	55	-		
	9:00			-	65	-		
	12:00			-	65	-		
Contrast Ratio	Cr		$\theta=0^{\circ}$ $\Phi=0^{\circ}$	300	500	-	-	4
Response Time	T _r +T _f			-	25	35	ms	5
							ms	
Color of CIE Coordinate	W	x	$\theta=0^{\circ}$ $\Phi=0^{\circ}$		0.313		-	1,6
		y			0.323		-	
	R	x			0.618		-	
		y			0.306		-	
	G	x			0.306		-	
		y			0.527		-	
	B	x			0.139		-	
		y			0.098		-	
NTSC Ratio	S				52	-	%	


Note: The parameter is slightly changed by temperature, driving voltage and materiel

Note 1: The data are measured after LEDs are turned on for 5 minutes. LCM displays full white. The brightness is the average value of 9 measured spots. Measurement equipment BM-7 ($\Phi 5mm$)

Measuring condition:

- Measuring surroundings: Dark room.
- Measuring temperature: $T_a = 25^\circ C$.
- Adjust operating voltage to get optimum contrast at the center of the display.

Measured value at the center point of LCD panel after more than 5 minutes while backlight turning on.




Note 2: The luminance uniformity is calculated by using following formula.

$$\Delta Bp = Bp (\text{Min.}) / Bp (\text{Max.}) \times 100 (\%)$$


$Bp (\text{Max.})$ = Maximum brightness in 9 measured spots

$Bp (\text{Min.})$ = Minimum brightness in 9 measured spots.




Note 3: The definition of viewing angle:

Refer to the graph below marked by ϑ and ϕ




Note 4: Definition of contrast ratio.(Test LCD using DMS501)



$$\text{Contrast ratio}(Cr) = \frac{\text{Brightness of selected dots}}{\text{Brightness of non-selected dots}}$$


Note 5: Definition of Response time. (Test LCD using DMS501):

The output signals of photo detector are measured when the input signals are changed from "black" to "white"(falling time) and from "white" to "black"(rising time), respectively. The response time is defined as the time interval between the 10% and 90% of amplitudes. Refer to figure as below.



The definition of response time

Note 6: Definition of Color of CIE Coordinate and NTSC Ratio.




Color gamut:

$$S = \frac{\text{area of RGB triangle}}{\text{area of NTSC triangle}} \times 100\%$$

Note 7: Definition of cross talk.

Cross talk ratio(%)=|pattern A Brightness-pattern B Brightness|/pattern A Brightness*100



Electric volume value=3F+/-3Hex

8. Reliability Test Items and Criteria

No	Test Item	Test condition	Criterion
1	High Temperature Storage	80°C±2°C 96H Restore 2H at 25°C Power off	<i>Note 1</i> <i>Note 2</i> <i>Note 3</i> <i>Note 4</i>
2	Low Temperature Storage	-30°C±2°C 96H Restore 2H at 25°C Power off	
3	High Temperature Operation	70°C±2°C 96H Restore 2H at 25°C Power on	
4	Low Temperature Operation	-20°C±2°C 96H Restore 4H at 25°C Power on	
5	High Temperature/Humidity Operation	60°C±2°C 90%RH 96H Power on	
6	Temperature Cycle	-30°C —————> 80°C 30min 5min 30min after 5 cycle, Restore 2H at 25°C Power off	

Note: Operation: Supply 3.3V for logic system.

The inspection terms after reliability test, as below

ITEM	Inspection
Contrast	CR>50%
IDD	IDD<200%
Brightness	Brightness>60%
Color Tone	Color Tone+/-0,05

Note 1:Ta is the ambient temperature of samples.

Note 2:Ts is the temperature of panel's surface.

Note 3:In the standard condition,there shall be no practical problem that may after the display function.After the reliability test,the product only guarantees operation,but don't guarantee all of the cosmetic specification.

Note4:Before cosmetic and function test,the product must have enough recovery time,at least 2 hours at room temperature.

9. Precautions for Use of LCD Modules

9.1 Handling Precautions

9.1.1 *The display panel is made of glass. Do not subject it to a mechanical shock by dropping it from a high place, etc.*

9.1.2 *If the display panel is damaged and the liquid crystal substance inside it leaks out, be sure not to get any in your mouth, if the substance comes into contact with your skin or clothes, promptly wash it off using soap and water.*

9.1.3 *Do not apply excessive force to the display surface or the adjoining areas since this may cause the color tone to vary.*

9.1.4 *The polarizer covering the display surface of the LCD module is soft and easily scratched. Handle this polarizer carefully.*

9.1.5 *If the display surface is contaminated, breathe on the surface and gently wipe it with a soft dry cloth. If still not completely clear, moisten cloth with one of the following solvents:*

— Isopropyl alcohol — Ethyl alcohol

Solvents other than those mentioned above may damage the polarizer. Especially, do not use the following:

— Water — Ketone — Aromatic solvents

9.1.6 *Do not attempt to disassemble the LCD Module.*

9.1.7 *If the logic circuit power is off, do not apply the input signals.*

9.1.8 *To prevent destruction of the elements by static electricity, be careful to maintain an optimum work environment.*

a. Be sure to ground the body when handling the LCD Modules.

b. Tools required for assembly, such as soldering irons, must be properly ground.

c. To reduce the amount of static electricity generated, do not conduct assembly and other work under dry conditions.

d. The LCD Module is coated with a film to protect the display surface. Be care when peeling off this protective film since static electricity may be generated.

9.2 Storage precautions

9.2.1 When storing the LCD modules, avoid exposure to direct sunlight or to the light of fluorescent lamps.

9.2.2 The LCD modules should be stored under the storage temperature range. If the LCD modules will be stored for a long time, the recommend condition is:

Temperature : $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$

Relatively humidity: $\leq 80\%$

9.2.3 The LCD modules should be stored in the room without acid, alkali and harmful gas.

9.3 The LCD modules should be no falling and violent shocking during transportation, and also should avoid excessive press, water, damp and sunshine.

END