

Applications Commercial Grade


Applications Detail Audio Line

Feature For FM Band

Series MAF

Status Production

Brand TDK



Size

Length(L)	1.00mm ±0.05mm
Width(W)	0.50mm ±0.05mm
Thickness(T)	0.70mm ±0.05mm
Recommended Land Pattern (A)	0.50mm Nom.
Recommended Land Pattern (B)	0.40mm Nom.
Recommended Land Pattern (C)	0.50mm Nom.

Electrical Characteristics



Impedance (Typ.) at 1MHz	
Impedance (Typ.) at 100MHz	1kΩ
Impedance (Typ.) at 900MHz	
Impedance (Typ.) at 1.7GHz	
Rated Current	230mA
DC Resistance (Typ.)	750mΩ
DC Resistance (Max.)	900mΩ

Other

Operating Temp. Range (Including Self-Temp. Rise)	-55 to 125°C
Soldering Method	Reflow
	Iron Soldering
Packing	Punched (Paper)Taping [180mm Reel, Tape width 8mm]
Package Quantity	8000pcs
Weight	0.001g

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.

Characteristic Graphs(This is reference data, and does not guarantee the products characteristics.)



! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.

Associated Images

