

LENINA-M

~30° medium beam

TECHNICAL SPECIFICATIONS:

Dimensions	Ø 74.0 mm
Height	40 mm
Fastening	socket
ROHS compliant	yes ⓘ


MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish	Coating
LENINA-M	Reflector	PC	metal		lacquer



ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
C12598_LENINA-M » Box size: 476 x 273 x 197 mm	60	120	60	2.0




See also our general installation guide: www.ledil.com/installation_guide


PHOTOMETRIC DATA (MEASURED):



LED BXRA ES Rectangle
FWHM / FWTM 36.0° / 76.0°
Efficiency 78 %
LEDs/each optic 1
Light colour White
Required components:
C12153_LENINA-STD-BASE-BXRA
C12606_LENINA-DL




LED BXRA ES Rectangle
FWHM / FWTM 29.0° / 75.0°
Efficiency 86 %
LEDs/each optic 1
Light colour White
Required components:
C12153_LENINA-STD-BASE-BXRA



LED BXRA RS
FWHM / FWTM 47.0° / 89.0°
Efficiency 80 %
Peak intensity 1.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12229_LENINA-STD-BASE-RS
C12606_LENINA-DL



LED BXRA RS
FWHM / FWTM 44.0° / 82.0°
Efficiency 88 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12229_LENINA-STD-BASE-RS




PHOTOMETRIC DATA (MEASURED):



LED V10 Gen6
FWHM / FWTM 21.0° / 68.0°
Efficiency 84 %
Peak intensity 3.2 cd/lm
LEDs/each optic 1
Light colour White

Required components:



C13186_LENINA-STD-BASE-CXA15
C12606_LENINA-DL



LED Vero SE 29
FWHM / FWTM 51.0° / 84.0°
Efficiency 92 %
Peak intensity 1.2 cd/lm
LEDs/each optic 1
Light colour White

Required components:


C15083_LENINA-STD-BASE-VERO29



LED VERO13
FWHM / FWTM 31.0° / 74.0°
Efficiency 87 %
Peak intensity 2 cd/lm
LEDs/each optic 1
Light colour White

Required components:


C13868_LENINA-STD-BASE-VERO13-18
C12606_LENINA-DL



LED VERO13
FWHM / FWTM 28.0° / 74.0°
Efficiency 91 %
Peak intensity 2.4 cd/lm
LEDs/each optic 1
Light colour White

Required components:


C13868_LENINA-STD-BASE-VERO13-18




PHOTOMETRIC DATA (MEASURED):




LED VERO18
FWHM / FWTM 37.0° / 77.0°
Efficiency 86 %
Peak intensity 1.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENINA-STD-BASE-VERO13-18
C12606_LENINA-DL




LED VERO18
FWHM / FWTM 35.0° / 76.0°
Efficiency 90 %
Peak intensity 1.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENINA-STD-BASE-VERO13-18



LED VERO29
FWHM / FWTM 52.0° / 85.0°
Efficiency 85 %
Peak intensity 1.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13867_LENINA-STD-BASE-VERO29
C12606_LENINA-DL





LED VERO29
FWHM / FWTM 52.0° / 84.0°
Efficiency 89 %
Peak intensity 1.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13867_LENINA-STD-BASE-VERO29



PHOTOMETRIC DATA (MEASURED):

CITIZEN

LED CL-L340
FWHM / FWTM 26.0° / 71.0°
Efficiency 92 %
Peak intensity 2.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C11995_LENINA-STD-BASE-CL340



CITIZEN



LED CL-L340
FWHM / FWTM 35.0° / 76.0°
Efficiency 78 %
LEDs/each optic 1
Light colour White
Required components:
C11995_LENINA-STD-BASE-CL340
C12606_LENINA-DL

CITIZEN

LED CL-L340
FWHM / FWTM 30.0° / 74.0°
Efficiency 86 %
LEDs/each optic 1
Light colour White
Required components:
C11995_LENINA-STD-BASE-CL340

CITIZEN



LED CLL02x/CLU02x (LES10)
FWHM / FWTM 23.0° / 71.0°
Efficiency 91 %
Peak intensity 3 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENINA-STD-BASE-VERO13-18
Bender Wirth: 434 Typ L1



PHOTOMETRIC DATA (MEASURED):



CITIZEN

LED CLL02x/CLU02x (LES10)
 FWHM / FWTM 26.0° / 71.0°
 Efficiency 87 %
 Peak intensity 2.3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13868_LENINA-STD-BASE-VERO13-18
 C12606_LENINA-DL
 Bender Wirth: 434 Typ L1





CITIZEN

LED CLL03x/CLU03x
 FWHM / FWTM 30.0° / 73.0°
 Efficiency 87 %
 Peak intensity 2 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C12691_LENINA-STD-BASE-CLL030
 C12606_LENINA-DL





CITIZEN

LED CLL03x/CLU03x
 FWHM / FWTM 29.0° / 73.0°
 Efficiency 91 %
 Peak intensity 2.3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13868_LENINA-STD-BASE-VERO13-18
 Bender Wirth: 433 Typ L1



CITIZEN



LED CLL03x/CLU03x
 FWHM / FWTM 28.0° / 73.0°
 Efficiency 91 %
 Peak intensity 2.4 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C12691_LENINA-STD-BASE-CLL030



PHOTOMETRIC DATA (MEASURED):



CITIZEN

LED CLL03x/CLU03x
FWHM / FWTM 31.0° / 73.0°
Efficiency 88 %
Peak intensity 2 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENINA-STD-BASE-VERO13-18
C12606_LENINA-DL
Bender Wirth: 433 Typ L1





CITIZEN

LED CLL04x/CLU04x
FWHM / FWTM 40.0° / 78.0°
Efficiency 87 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13867_LENINA-STD-BASE-VERO29
C12606_LENINA-DL
Bender Wirth: 431 Typ L3





CITIZEN

LED CLL04x/CLU04x
FWHM / FWTM 38.0° / 77.0°
Efficiency 76 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12606_LENINA-DL
A.A.G. STUCCHI: 8102-G2 + S-8000-12



CITIZEN


LED CLL04x/CLU04x
FWHM / FWTM 39.0° / 78.0°
Efficiency 92 %
Peak intensity 1.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13867_LENINA-STD-BASE-VERO29
Bender Wirth: 431 Typ L3



PHOTOMETRIC DATA (MEASURED):



CITIZEN

LED CLL04x/CLU04x
FWHM / FWTM 37.0° / 76.0°
Efficiency 87 %
Peak intensity 1.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12606_LENINA-DL
IDEAL: 50-2204CT + 50-2100LN





CITIZEN

LED CLL04x/CLU04x
FWHM / FWTM 43.0° / 80.0°
Efficiency 78 %
Peak intensity 1.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12692_LENINA-STD-BASE-CLL040
C12606_LENINA-DL





CITIZEN

LED CLL04x/CLU04x
FWHM / FWTM 36.0° / 76.0°
Efficiency 83 %
Peak intensity 1.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:
A.A.G. STUCCHI: 8102-G2 + S-8000-12



CITIZEN



LED CLL04x/CLU04x
FWHM / FWTM 35.0° / 75.0°
Efficiency 90 %
Peak intensity 1.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:
IDEAL: 50-2204CT + 50-2100LN



PHOTOMETRIC DATA (MEASURED):


CITIZEN

LED CLL04x/CLU04x
FWHM / FWTM 40.0° / 77.0°
Efficiency 86 %
Peak intensity 1.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12692_LENINA-STD-BASE-CLL040





CITIZEN

LED CLU700/701/702
FWHM / FWTM 17.0° / 60.0°
Efficiency 91 %
Peak intensity 3.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENINA-STD-BASE-VERO13-18
Bender Wirth: 434 Typ L1





CITIZEN

LED CLU700/701/702
FWHM / FWTM 23.0° / 70.0°
Efficiency 87 %
Peak intensity 2.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENINA-STD-BASE-VERO13-18
C12606_LENINA-DL
Bender Wirth: 434 Typ L1



CITIZEN



LED CLU710/711
FWHM / FWTM 24.0° / 71.0°
Efficiency 89 %
Peak intensity 2.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12691_LENINA-STD-BASE-CLL030
C12606_LENINA-DL



PHOTOMETRIC DATA (MEASURED):



CITIZEN

LED CLU710/711
FWHM / FWTM 19.0° / 68.0°
Efficiency 93 %
Peak intensity 3.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12691_LENINA-STD-BASE-CLL030





CITIZEN

LED CLU720/721
FWHM / FWTM 26.0° / 72.0°
Efficiency 84 %
Peak intensity 2.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12691_LENINA-STD-BASE-CLL030
C12606_LENINA-DL





CITIZEN

LED CLU720/721
FWHM / FWTM 23.0° / 71.0°
Efficiency 88 %
Peak intensity 2.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12691_LENINA-STD-BASE-CLL030



CITIZEN



LED CLU730/731
FWHM / FWTM 26.0° / 71.0°
Efficiency 84 %
Peak intensity 2.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12692_LENINA-STD-BASE-CLL040
C12606_LENINA-DL



PHOTOMETRIC DATA (MEASURED):



CITIZEN

LED CLU730/731
FWHM / FWTM 24.0° / 70.0°
Efficiency 94 %
Peak intensity 2.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12692_LENINA-STD-BASE-CLL040





CREE LED

LED CMA1840
FWHM / FWTM 25.0° / 70.0°
Efficiency 92 %
Peak intensity 2.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C14146_LENINA-STD-BASE-CXA18





CREE LED

LED CMA1840
FWHM / FWTM 25.0° / 70.0°
Efficiency 92 %
Peak intensity 2.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C14146_LENINA-STD-BASE-CXA18



CREE LED


LED CMA2550
FWHM / FWTM 32.0° / 73.0°
Efficiency 92 %
Peak intensity 2.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13324_LENINA-STD-BASE-CXA25



PHOTOMETRIC DATA (MEASURED):





LED CMT14xx
FWHM / FWTM 25.0° / 73.0°
Efficiency 92 %
Peak intensity 2.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENINA-STD-BASE-VERO13-18
Bender Wirth: 434 Typ L1





LED CMT19xx
FWHM / FWTM 29.0° / 73.0°
Efficiency 92 %
Peak intensity 2.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12691_LENINA-STD-BASE-CLL030



LED CMT19xx
FWHM / FWTM 30.0° / 74.0°
Efficiency 92 %
Peak intensity 2.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENINA-STD-BASE-VERO13-18
Bender Wirth: 477 Typ L1




LED CMT28xx
FWHM / FWTM 39.0° / 77.0°
Efficiency 92 %
Peak intensity 1.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13867_LENINA-STD-BASE-VERO29
Bender Wirth: 471 Typ L3




PHOTOMETRIC DATA (MEASURED):




LED CMT28xx
FWHM / FWTM 37.0° / 76.0°
Efficiency 92 %
Peak intensity 1.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12692_LENINA-STD-BASE-CLL040





LED CXA/B 15xx
FWHM / FWTM 22.0°
Efficiency %
Peak intensity 3.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENINA-STD-BASE-VERO13-18
Bender Wirth: 441 Typ L1



LED CXA/B 15xx
FWHM / FWTM 22.0° / 66.0°
Efficiency 86 %
Peak intensity 3.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13186_LENINA-STD-BASE-CXA15
C12606_LENINA-DL




LED CXA/B 15xx
FWHM / FWTM 26.0° / 71.0°
Efficiency 87 %
Peak intensity 2.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENINA-STD-BASE-VERO13-18
C12606_LENINA-DL
Bender Wirth: 441 Typ L1



PHOTOMETRIC DATA (MEASURED):



CREE LED

LED CXA/B 15xx
FWHM / FWTM 17.0° / 56.0°
Efficiency 91 %
Peak intensity 4.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13186_LENINA-STD-BASE-CXA15





CREE LED

LED CXA/B 1816 & CXA/B 1820 & CXA 1850
FWHM / FWTM 21.0° / 72.0°
Efficiency 92 %
Peak intensity 3.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C14146_LENINA-STD-BASE-CXA18





CREE LED

LED CXA/B 1816 & CXA/B 1820 & CXA 1850
FWHM / FWTM 26.0° / 73.0°
Efficiency 92 %
Peak intensity 2.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENINA-STD-BASE-VERO13-18
Bender Wirth: 437 Typ L1



CREE LED

LED CXA/B 1816 & CXA/B 1820 & CXA 1850
FWHM / FWTM 29.0° / 73.0°
Efficiency 88 %
Peak intensity 2.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENINA-STD-BASE-VERO13-18
C12606_LENINA-DL
Bender Wirth: 437 Typ L1



PHOTOMETRIC DATA (MEASURED):





LED CXA/B 1830
FWHM / FWTM 33.0° / 74.0°
Efficiency 88 %
Peak intensity 1.9 cd/lm
LEDs/each optic 1
Light colour White

Required components:

C13868_LENINA-STD-BASE-VERO13-18

C12606_LENINA-DL

Bender Wirth: 437 Typ L1





LED CXA/B 1830
FWHM / FWTM 30.0° / 74.0°
Efficiency 93 %
Peak intensity 2.3 cd/lm
LEDs/each optic 1
Light colour White

Required components:

C13868_LENINA-STD-BASE-VERO13-18

Bender Wirth: 437 Typ L1





LED CXA/B 25xx
FWHM / FWTM 35.0° / 74.0°
Efficiency 78 %
Peak intensity 1.6 cd/lm
LEDs/each optic 1
Light colour White

Required components:

C13324_LENINA-STD-BASE-CXA25



C12606_LENINA-DL



LED CXA/B 25xx
FWHM / FWTM 33.0° / 74.0°
Efficiency 86 %
Peak intensity 1.9 cd/lm
LEDs/each optic 1
Light colour White

Required components:


C13324_LENINA-STD-BASE-CXA25




PHOTOMETRIC DATA (MEASURED):




LED CXA2011
FWHM / FWTM 33.0° / 76.0°
Efficiency 77 %
Peak intensity 1.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12105_LENINA-STD-BASE-CXA20
C12606_LENINA-DL




LED CXA2011
FWHM / FWTM 28.0° / 73.0°
Efficiency 85 %
Peak intensity 2.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12105_LENINA-STD-BASE-CXA20



LED CHI3030 19W
FWHM / FWTM 39.0° / 80.0°
Efficiency 91 %
Peak intensity 1.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13867_LENINA-STD-BASE-VERO29
C12606_LENINA-DL
Bender Wirth: 468 Typ L3





LED CHI3030 29W
FWHM / FWTM 47.0° / 84.0°
Efficiency 87 %
Peak intensity 1.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13867_LENINA-STD-BASE-VERO29
C12606_LENINA-DL
Bender Wirth: 468 Typ L3





PHOTOMETRIC DATA (MEASURED):




LED LUXEON CoB 1202/1203
FWHM / FWTM 22.0° / 71.0°
Efficiency 92 %
Peak intensity 3.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENINA-STD-BASE-VERO13-18
Bender Wirth: 438 Typ L1




LED LUXEON CoB 1202/1203
FWHM / FWTM 26.0° / 71.0°
Efficiency 88 %
Peak intensity 2.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENINA-STD-BASE-VERO13-18
C12606_LENINA-DL
Bender Wirth: 438 Typ L1



LED LUXEON CoB 1204/1205
FWHM / FWTM 28.0° / 74.0°
Efficiency 87 %
Peak intensity 2.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12292_LENINA-STD-BASE-MEZ





LED LUXEON CoB 1204/1205
FWHM / FWTM 30.0° / 74.0°
Efficiency 82 %
Peak intensity 1.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12292_LENINA-STD-BASE-MEZ
C12606_LENINA-DL





PHOTOMETRIC DATA (MEASURED):




LED LUXEON CoB 1204HD
FWHM / FWTM 20.0° / 65.0°
Efficiency 92 %
Peak intensity 3.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C11981_LENINA-STD-BASE-COB-L110





LED LUXEON CoB 1205HD
FWHM / FWTM 23.0° / 70.0°
Efficiency 92 %
Peak intensity 3 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C11981_LENINA-STD-BASE-COB-L110



LED LUXEON CoB 1208
FWHM / FWTM 31.0° / 75.0°
Efficiency 88 %
Peak intensity 2 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12292_LENINA-STD-BASE-MEZ





LED LUXEON CoB 1208
FWHM / FWTM 33.0° / 75.0°
Efficiency 83 %
Peak intensity 1.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12292_LENINA-STD-BASE-MEZ
C12606_LENINA-DL





PHOTOMETRIC DATA (MEASURED):





LED LUXEON CoB 1211
 FWHM / FWTM 37.0° / 77.0°
 Efficiency 87 %
 Peak intensity 1.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13867_LENINA-STD-BASE-VERO29
 C12606_LENINA-DL
 Bender Wirth: 431 Typ L3




LED LUXEON CoB 1211
 FWHM / FWTM 35.0° / 76.0°
 Efficiency 93 %
 Peak intensity 1.9 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13867_LENINA-STD-BASE-VERO29
 Bender Wirth: 431 Typ L3



LED LUXEON CoB 1216/1812
 FWHM / FWTM 39.0° / 77.0°
 Efficiency 81 %
 Peak intensity 1.4 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C12606_LENINA-DL
 A.A.G. STUCCHI: 8102-G2 + S-8000-12




LED LUXEON CoB 1216/1812
 FWHM / FWTM 40.0° / 77.0°
 Efficiency 88 %
 Peak intensity 1.5 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C12692_LENINA-STD-BASE-CLL040
 C12606_LENINA-DL





PHOTOMETRIC DATA (MEASURED):




LED LUXEON CoB 1216/1812
 FWHM / FWTM 39.0° / 76.0°
 Efficiency 92 %
 Peak intensity 1.7 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C12692_LENINA-STD-BASE-CLL040




LED LUXEON CoB 1216/1812
 FWHM / FWTM 38.0° / 77.0°
 Efficiency 85 %
 Peak intensity 1.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 A.A.G. STUCCHI: 8102-G2 + S-8000-12



LED LUXEON K12
 FWHM / FWTM 30.0° / 73.0°
 Efficiency 83 %
 Peak intensity 1.9 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C12924_LENINA-STD-BASE-LUXEON-K
 C12606_LENINA-DL




LED LUXEON K12
 FWHM / FWTM 28.0° / 74.0°
 Efficiency 89 %
 Peak intensity 2.3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C12924_LENINA-STD-BASE-LUXEON-K




PHOTOMETRIC DATA (MEASURED):





LED LUXEON K16
 FWHM / FWTM 30.0° / 74.0°
 Efficiency 85 %
 Peak intensity 2 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C12924_LEN-STD-BASE-LUXEON-K





LED LUXEON K16
 FWHM / FWTM 34.0° / 75.0°
 Efficiency 79 %
 Peak intensity 1.5 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C12924_LEN-STD-BASE-LUXEON-K
 C12606_LENINA-DL



LED CDM-14 (Dim-To-Warm)
 FWHM / FWTM 31.0° / 74.0°
 Efficiency 88 %
 Peak intensity 1.9 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13868_LEN-STD-BASE-VERO13-18
 C12606_LENINA-DL
 Bender Wirth: 491 Typ L2





LED CDM-14 (Dim-To-Warm)
 FWHM / FWTM 29.0° / 74.0°
 Efficiency 92 %
 Peak intensity 2.3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13868_LEN-STD-BASE-VERO13-18
 Bender Wirth: 491 Typ L2





PHOTOMETRIC DATA (MEASURED):





LED CDM-18 (Dim-To-Warm)
 FWHM / FWTM 36.0° / 76.0°
 Efficiency 88 %
 Peak intensity 1.7 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13868_LENINA-STD-BASE-VERO13-18
 C12606_LENINA-DL
 Bender Wirth: 491 Typ L2





LED CDM-18 (Dim-To-Warm)
 FWHM / FWTM 34.0° / 75.0°
 Efficiency 92 %
 Peak intensity 2 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13868_LENINA-STD-BASE-VERO13-18
 Bender Wirth: 491 Typ L2



LED CDM-9 (Dim-To-Warm)
 FWHM / FWTM 27.0° / 72.0°
 Efficiency 87 %
 Peak intensity 2.2 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13868_LENINA-STD-BASE-VERO13-18
 C12606_LENINA-DL
 Bender Wirth: 490 Typ L1





LED CDM-9 (Dim-To-Warm)
 FWHM / FWTM 24.0° / 72.0°
 Efficiency 92 %
 Peak intensity 2.9 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13868_LENINA-STD-BASE-VERO13-18
 Bender Wirth: 490 Typ L1





PHOTOMETRIC DATA (MEASURED):





LED CTM-14 (Tunable White)
 FWHM / FWTM 31.0° / 74.0°
 Efficiency 87 %
 Peak intensity 1.9 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13867_LENINA-STD-BASE-VERO29
 C12606_LENINA-DL
 Bender Wirth: 442 Typ L3





LED CTM-14 (Tunable White)
 FWHM / FWTM 28.0° / 74.0°
 Efficiency 92 %
 Peak intensity 2.4 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13867_LENINA-STD-BASE-VERO29
 Bender Wirth: 442 Typ L3



LED CTM-18 (Tunable White)
 FWHM / FWTM 34.0° / 76.0°
 Efficiency 87 %
 Peak intensity 1.7 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13867_LENINA-STD-BASE-VERO29
 C12606_LENINA-DL
 Bender Wirth: 442 Typ L3





LED CTM-18 (Tunable White)
 FWHM / FWTM 32.0° / 76.0°
 Efficiency 92 %
 Peak intensity 2 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13867_LENINA-STD-BASE-VERO29
 Bender Wirth: 442 Typ L3





PHOTOMETRIC DATA (MEASURED):





LED CTM-22 (Tunable White)
 FWHM / FWTM 40.0° / 79.0°
 Efficiency 87 %
 Peak intensity 1.4 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13867_LENINA-STD-BASE-VERO29
 C12606_LENINA-DL
 Bender Wirth: 494 Typ L3





LED CTM-22 (Tunable White)
 FWHM / FWTM 39.0° / 79.0°
 Efficiency 92 %
 Peak intensity 1.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13867_LENINA-STD-BASE-VERO29
 Bender Wirth: 494 Typ L3



LED CxM-14 (19x19)
 FWHM / FWTM 31.0° / 73.0°
 Efficiency 89 %
 Peak intensity 2.1 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C12691_LENINA-STD-BASE-CLL030
 C12606_LENINA-DL




LED CxM-14 (19x19)
 FWHM / FWTM 28.0° / 72.0°
 Efficiency 93 %
 Peak intensity 2.5 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C12691_LENINA-STD-BASE-CLL030




PHOTOMETRIC DATA (MEASURED):





LED CxM-22 (28x28)
FWHM / FWTM 40.0° / 80.0°
Efficiency 89 %
Peak intensity 1.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12692_LENINA-STD-BASE-CLL040
C12606_LENINA-DL





LED CxM-22 (28x28)
FWHM / FWTM 39.0° / 80.0°
Efficiency 92 %
Peak intensity 1.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12692_LENINA-STD-BASE-CLL040



LED COB J-Type
FWHM / FWTM 33.0° / 75.0°
Efficiency 81 %
Peak intensity 1.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12292_LENINA-STD-BASE-MEZ
C12606_LENINA-DL



LED COB J-Type
FWHM / FWTM 31.0° / 75.0°
Efficiency 86 %
Peak intensity 1.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12292_LENINA-STD-BASE-MEZ




PHOTOMETRIC DATA (MEASURED):



LED COB J-Type
FWHM / FWTM 29.0° / 74.0°
Efficiency 93 %
Peak intensity 2.3 cd/lm
LEDs/each optic 1
Light colour White

Required components:



C13868_LENINA-STD-BASE-VERO13-18
Bender Wirth: 463 Typ L2



LED COB J-Type
FWHM / FWTM 32.0° / 74.0°
Efficiency 89 %
Peak intensity 1.9 cd/lm
LEDs/each optic 1
Light colour White

Required components:



C13868_LENINA-STD-BASE-VERO13-18
C12606_LENINA-DL



LED COB L-Type (LES 11)
FWHM / FWTM 29.0° / 73.0°
Efficiency 79 %
Peak intensity 1.8 cd/lm
LEDs/each optic 1
Light colour White

Required components:



C11981_LENINA-STD-BASE-COB-L110
C12606_LENINA-DL



LED COB L-Type (LES 11)
FWHM / FWTM 27.0° / 74.0°
Efficiency 84 %
Peak intensity 2.2 cd/lm
LEDs/each optic 1
Light colour White

Required components:


C11981_LENINA-STD-BASE-COB-L110





PHOTOMETRIC DATA (MEASURED):





LED COB L-Type (LES 11)
 FWHM / FWTM 25.0° / 72.0°
 Efficiency 91 %
 Peak intensity 2.7 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13868_LENINA-STD-BASE-VERO13-18
 Bender Wirth: 438 Typ L1





LED COB L-Type (LES 11)
 FWHM / FWTM 28.0° / 72.0°
 Efficiency 87 %
 Peak intensity 2.2 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13868_LENINA-STD-BASE-VERO13-18
 C12606_LENINA-DL
 Bender Wirth: 438 Typ L1



LED COB L-Type (LES 9)
 FWHM / FWTM 26.0° / 71.0°
 Efficiency 89 %
 Peak intensity 2.4 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13868_LENINA-STD-BASE-VERO13-18
 C12606_LENINA-DL
 Bender Wirth: 438 Typ L1





LED NVCWJ024Z-V1MT: COB J-Type Tunable White
 FWHM / FWTM 29.0° / 73.0°
 Efficiency 87 %
 Peak intensity 2 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13868_LENINA-STD-BASE-VERO13-18
 C12606_LENINA-DL
 Bender Wirth: 498 Typ L2





PHOTOMETRIC DATA (MEASURED):





LED NVCWJ024Z-V1MT: COB J-Type Tunable White
 FWHM / FWTM 26.0° / 73.0°
 Efficiency 92 %
 Peak intensity 2.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13868_LENINA-STD-BASE-VERO13-18
 Bender Wirth: 498 Typ L2





LED Soleriq S13
 FWHM / FWTM 30.0° / 73.0°
 Efficiency 87 %
 Peak intensity 2 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13868_LENINA-STD-BASE-VERO13-18
 C12606_LENINA-DL
 Bender Wirth: 437 Typ L1



LED Soleriq S13
 FWHM / FWTM 27.0° / 73.0°
 Efficiency 91 %
 Peak intensity 2.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13868_LENINA-STD-BASE-VERO13-18
 Bender Wirth: 437 Typ L1



LED Soleriq S19
 FWHM / FWTM 34.0° / 76.0°
 Efficiency 89 %
 Peak intensity 1.7 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13867_LENINA-STD-BASE-VERO29
 C12606_LENINA-DL
 Bender Wirth: 462 Typ L3



PHOTOMETRIC DATA (MEASURED):

OSRAM



Opto Semiconductors

LED Soleriq S19
FWHM / FWTM 32.0° / 76.0°
Efficiency 93 %
Peak intensity 2 cd/lm
LEDs/each optic 1
Light colour White

Required components:

C13867_LENINA-STD-BASE-VERO29

Bender Wirth: 462 Typ L3




PHILIPS

LED Fortimo SLM L13 CoB
FWHM / FWTM 30.0° / 72.0°
Efficiency 86 %
Peak intensity 2 cd/lm
LEDs/each optic 1
Light colour White

Required components:

C12292_LENINA-STD-BASE-MEZ

C12606_LENINA-DL




PHILIPS

LED Fortimo SLM L13 CoB
FWHM / FWTM 27.0° / 72.0°
Efficiency 93 %
Peak intensity 2.6 cd/lm
LEDs/each optic 1
Light colour White

Required components:

C12292_LENINA-STD-BASE-MEZ





PHILIPS

LED Fortimo SLM L15 CoB
FWHM / FWTM 32.0° / 74.0°
Efficiency 86 %
Peak intensity 1.8 cd/lm
LEDs/each optic 1
Light colour White

Required components:

C12292_LENINA-STD-BASE-MEZ



C12606_LENINA-DL



PHOTOMETRIC DATA (MEASURED):



PHILIPS

LED Fortimo SLM L15 CoB
FWHM / FWTM 29.0° / 73.0°
Efficiency %
Peak intensity 2.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12292_LENINA-STD-BASE-MEZ





PHILIPS

LED Fortimo SLM L19 CoB
FWHM / FWTM 35.0° / 75.0°
Efficiency 86 %
Peak intensity 1.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12692_LENINA-STD-BASE-CLL040
C12606_LENINA-DL





PHILIPS

LED Fortimo SLM L19 CoB
FWHM / FWTM 33.0° / 74.0°
Efficiency 92 %
Peak intensity 2 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12692_LENINA-STD-BASE-CLL040



PHILIPS



LED Fortimo SLM L23 CoB
FWHM / FWTM 39.0° / 76.0°
Efficiency 92 %
Peak intensity 1.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12692_LENINA-STD-BASE-CLL040



PHOTOMETRIC DATA (MEASURED):



PHILIPS

LED Fortimo SLM L23 CoB
FWHM / FWTM 40.0° / 77.0°
Efficiency 86 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12692_LENINA-STD-BASE-CLL040
C12606_LENINA-DL





SAMSUNG

LED LC016D / LC019D / LC026D / LC033D
FWHM / FWTM 30.0° / 74.0°
Efficiency 92 %
Peak intensity 2.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12691_LENINA-STD-BASE-CLL030





SAMSUNG

LED LC016D / LC019D / LC026D / LC033D
FWHM / FWTM 33.0° / 75.0°
Efficiency 87 %
Peak intensity 1.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12691_LENINA-STD-BASE-CLL030
C12606_LENINA-DL



SAMSUNG



LED LC026B / 033B / 040B
FWHM / FWTM 33.0° / 75.0°
Efficiency 92 %
Peak intensity 2 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENINA-STD-BASE-VERO13-18
Bender Wirth: 450 Typ L2



PHOTOMETRIC DATA (MEASURED):



SAMSUNG

LED LC026B / 033B / 040B
 FWHM / FWTM 35.0° / 76.0°
 Efficiency 88 %
 Peak intensity 1.7 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13868_LENINA-STD-BASE-VERO13-18
 C12606_LENINA-DL
 Bender Wirth: 450 Typ L2





SAMSUNG

LED LC040D / LC060D / LC080D
 FWHM / FWTM 41.0° / 78.0°
 Efficiency 87 %
 Peak intensity 1.4 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C12692_LENINA-STD-BASE-CLL040
 C12606_LENINA-DL





SAMSUNG

LED LC040D / LC060D / LC080D
 FWHM / FWTM 40.0° / 77.0°
 Efficiency 91 %
 Peak intensity 1.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C12692_LENINA-STD-BASE-CLL040





SEOL SEMICONDUCTOR

LED ZC25/40/60
 FWHM / FWTM 44.0° / 79.0°
 Efficiency 81 %
 Peak intensity 1.2 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C12692_LENINA-STD-BASE-CLL040
 C12606_LENINA-DL





PHOTOMETRIC DATA (MEASURED):

SEOL SEOUL SEMICONDUCTOR LED ZC25/40/60 FWHM / FWTM 42.0° / 79.0° Efficiency 85 % Peak intensity 1.4 cd/lm LEDs/each optic 1 Light colour White Required components: C12692_LENINA-STD-BASE-CLL040		
SHARP LED Mega Zenigata (GW5DGC) FWHM / FWTM 22.0° / 73.0° Efficiency 78 % LEDs/each optic 1 Light colour White Required components: C12292_LENINA-STD-BASE-MEZ C12606_LENINA-DL		
SHARP LED Mega Zenigata (GW5DGC) FWHM / FWTM 21.0° / 72.0° Efficiency 86 % LEDs/each optic 1 Light colour White Required components: C12292_LENINA-STD-BASE-MEZ		
SHARP LED Mega Zenigata (GW6DME) FWHM / FWTM 30.0° / 75.0° Efficiency 87 % Peak intensity 2 cd/lm LEDs/each optic 1 Light colour White Required components: C12292_LENINA-STD-BASE-MEZ		

PHOTOMETRIC DATA (MEASURED):



SHARP

LED Mega Zenigata (GW6DME)
 FWHM / FWTM 32.0° / 74.0°
 Efficiency 82 %
 Peak intensity 1.7 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C12292_LENASTD-BASE-MEZ
 C12606_LENINA-DL





TRIDONIC

LED SLE G7 LES15
 FWHM / FWTM 30.0° / 74.0°
 Efficiency 93 %
 Peak intensity 2.3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C12691_LENASTD-BASE-CLL030





TRIDONIC

LED SLE G7 LES17 H
 FWHM / FWTM 31.0° / 74.0°
 Efficiency 91 %
 Peak intensity 2.1 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C14547_LENADAPTER-B



TRIDONIC



LED SLE G7 LES21 H
 FWHM / FWTM 37.0° / 76.0°
 Efficiency 91 %
 Peak intensity 1.7 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C14547_LENADAPTER-B



PHOTOMETRIC DATA (MEASURED):

XICATO


LED XOB 14.5 mm
FWHM / FWTM 29.0° / 74.0°
Efficiency 93 %
Peak intensity 2.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12691_LENINA-STD-BASE-CLL030




PHOTOMETRIC DATA (SIMULATED):




LED V10 Gen7
FWHM / FWTM 28.0° / 70.0°
Efficiency 86 %
Peak intensity 2.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENINA-STD-BASE-VERO13-18
C12606_LENINA-DL
Bender Wirth: 486 Typ L1




LED V10 Gen7
FWHM / FWTM 26.0° / 71.0°
Efficiency 91 %
Peak intensity 2.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENINA-STD-BASE-VERO13-18
Bender Wirth: 486 Typ L1



LED V13 Gen7
FWHM / FWTM 26.0° / 70.0°
Efficiency 87 %
Peak intensity 2.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12606_LENINA-DL
IDEAL: 50-2103CT + 50-2100AN




LED V13 Gen7
FWHM / FWTM 32.0° / 72.0°
Efficiency 86 %
Peak intensity 2 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENINA-STD-BASE-VERO13-18
C12606_LENINA-DL
Bender Wirth: 477 Typ L1




PHOTOMETRIC DATA (SIMULATED):




LED V13 Gen7
FWHM / FWTM 26.0° / 70.0°
Efficiency 90 %
Peak intensity 2.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:
IDEAL: 50-2103CT + 50-2100AN




LED V13 Gen7
FWHM / FWTM 31.0° / 73.0°
Efficiency 90 %
Peak intensity 2.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENINA-STD-BASE-VERO13-18
Bender Wirth: 477 Typ L1



LED V22 Gen7
FWHM / FWTM 42.0° / 80.0°
Efficiency 87 %
Peak intensity 1.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13867_LENINA-STD-BASE-VERO29
C12606_LENINA-DL
Bender Wirth: 431 Typ L3




LED V22 Gen7
FWHM / FWTM 42.0° / 80.0°
Efficiency 90 %
Peak intensity 1.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13867_LENINA-STD-BASE-VERO29
Bender Wirth: 431 Typ L3




PHOTOMETRIC DATA (SIMULATED):



LED CXA/B 30xx
FWHM / FWTM 30.0° / 72.0°
Efficiency 84 %
Peak intensity 2 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12606_LENINA-DL
IDEAL: 50-2234C + 50-2100LN



LED CXA/B 30xx
FWHM / FWTM 28.0° / 70.0°
Efficiency 89 %
Peak intensity 2.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
IDEAL: 50-2234C + 50-2100LN



LED CxM-14 (19x19)
FWHM / FWTM 29.0° / 73.0°
Efficiency 91 %
Peak intensity 2.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENINA-STD-BASE-VERO13-18
Bender Wirth: 433 Typ L1



LED CxM-14 (19x19)
FWHM / FWTM 31.0° / 73.0°
Efficiency 88 %
Peak intensity 2 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENINA-STD-BASE-VERO13-18
C12606_LENINA-DL
Bender Wirth: 433 Typ L1

PHOTOMETRIC DATA (SIMULATED):



LED CxM-9 (13.5x13.5)
 FWHM / FWTM 26.0° / 71.0°
 Efficiency 87 %
 Peak intensity 2.3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13868_LENINA-STD-BASE-VERO13-18
 C12606_LENINA-DL
 Bender Wirth: 434 Typ L1




LED CxM-9 (13.5x13.5)
 FWHM / FWTM 23.0° / 71.0°
 Efficiency 91 %
 Peak intensity 3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13868_LENINA-STD-BASE-VERO13-18
 Bender Wirth: 434 Typ L1



Opto Semiconductors



LED Soleriq S15
 FWHM / FWTM 30.0° / 71.0°
 Efficiency 90 %
 Peak intensity 2.4 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C12691_LENINA-STD-BASE-CLL030



SEOUL SEMICONDUCTOR

LED ZC12/18
 FWHM / FWTM 29.0° / 73.0°
 Efficiency 91 %
 Peak intensity 2.3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13868_LENINA-STD-BASE-VERO13-18
 Bender Wirth: 433 Typ L1

PHOTOMETRIC DATA (SIMULATED):

SEOUL SEMICONDUCTOR LED ZC12/18 FWHM / FWTM 32.0° / 72.0° Efficiency 84 % Peak intensity 1.8 cd/lm LEDs/each optic 1 Light colour White Required components: C12691_LENINA-STD-BASE-CLL030 C12606_LENINA-DL	
SEOUL SEMICONDUCTOR LED ZC12/18 FWHM / FWTM 26.0° / 70.0° Efficiency 89 % Peak intensity 2.7 cd/lm LEDs/each optic 1 Light colour White Required components: C12691_LENINA-STD-BASE-CLL030	
SEOUL SEMICONDUCTOR LED ZC12/18 FWHM / FWTM 31.0° / 73.0° Efficiency 88 % Peak intensity 2 cd/lm LEDs/each optic 1 Light colour White Required components: C13868_LENINA-STD-BASE-VERO13-18 C12606_LENINA-DL Bender Wirth: 433 Typ L1	
SEOUL SEMICONDUCTOR LED ZC4/6 FWHM / FWTM 26.0° / 71.0° Efficiency 87 % Peak intensity 2.3 cd/lm LEDs/each optic 1 Light colour White Required components: C13868_LENINA-STD-BASE-VERO13-18 C12606_LENINA-DL Bender Wirth: 434 Typ L1	

PHOTOMETRIC DATA (SIMULATED):

 SEOUL SEMICONDUCTOR	
LED	ZC4/6
FWHM / FWTM	23.0° / 71.0°
Efficiency	91 %
Peak intensity	3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	
C13868_LENINA-STD-BASE-VERO13-18	
Bender Wirth: 434 Typ L1	

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)