

## HEIDI-W

~32° wide beam

### TECHNICAL SPECIFICATIONS:


Dimensions	Ø 21.6 mm
Height	11.7 mm
Fastening	pin, tape
ROHS compliant	yes ⓘ


### MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
HEIDI-W	Single lens	PMMA	clear	
HEIDI-TAPE	Tape	Acrylic foam	black	

### ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
CA11268_HEIDI-W	Single lens	3264	204	204	10.8
» Box size: 480 x 280 x 300 mm					





See also our general installation guide: [www.ledil.com/installation\\_guide](http://www.ledil.com/installation_guide)


### PHOTOMETRIC DATA (MEASURED):

#### CREE LED

LED XB-D  
FWHM / FWTM 30.0°  
Efficiency 88 %  
Peak intensity 2.6 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:


#### CREE LED

LED XB-H  
FWHM / FWTM 33.0° / 54.0°  
Efficiency 88 %  
Peak intensity 2.3 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:





#### CREE LED

LED XP-E  
FWHM / FWTM 32.0° / 50.0°  
Efficiency 92 %  
Peak intensity 2.7 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



#### CREE LED


LED XP-E2  
FWHM / FWTM 33.0° / 49.0°  
Efficiency 89 %  
Peak intensity 3 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



#### PHOTOMETRIC DATA (MEASURED):


##### CREE LED

LED XP-G  
FWHM / FWTM 31.0° / 52.0°  
Efficiency 92 %  
Peak intensity 2.5 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:





##### CREE LED

LED XQ-E HD  
FWHM / FWTM 29.0° / 44.0°  
Efficiency 94 %  
Peak intensity 3.8 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:





##### CREE LED

LED XQ-E HI  
FWHM / FWTM 34.0° / 50.0°  
Efficiency 93 %  
Peak intensity 2.8 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



##### LUMILEDS



LED LUXEON C  
FWHM / FWTM 31.0° / 49.0°  
Efficiency 88 %  
Peak intensity 3 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



#### PHOTOMETRIC DATA (MEASURED):


##### LUMILEDS

LED LUXEON CZ  
FWHM / FWTM 34.0° / 49.0°  
Efficiency 94 %  
Peak intensity 3.1 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:





##### LUMILEDS

LED LUXEON T  
FWHM / FWTM 31.0° / 51.0°  
Efficiency 87 %  
Peak intensity 2.8 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



##### LUMILEDS

LED LUXEON TX  
FWHM / FWTM 33.0° / 52.0°  
Efficiency 88 %  
Peak intensity 2.7 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:




##### NICHIA

LED NCSxx19A  
FWHM / FWTM 32.0° / 51.0°  
Efficiency 86 %  
Peak intensity 2.5 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:

#### PHOTOMETRIC DATA (MEASURED):





LED NCSxx19B  
FWHM / FWTM 33.0° / 52.0°  
Efficiency 88 %  
Peak intensity 2.8 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:




LED NVSxx19A  
FWHM / FWTM 32.0° / 54.0°  
Efficiency 86 %  
Peak intensity 2.3 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



LED OSLON Square CSSRM2/CSSRM3  
FWHM / FWTM 32.0° / 54.0°  
Efficiency 86 %  
Peak intensity 3 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



LED OSLON SSL 150  
FWHM / FWTM 32.0° / 50.0°  
Efficiency 88 %  
Peak intensity 2.8 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:






#### PHOTOMETRIC DATA (MEASURED):

#### OSRAM



Opto Semiconductors

LED OSLOM SSL 80  
FWHM / FWTM 32.0° / 50.0°  
Efficiency 86 %  
Peak intensity 2.7 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:





#### SAMSUNG

LED LH181A  
FWHM / FWTM 31.0° / 55.0°  
Efficiency 94 %  
Peak intensity 2.5 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:





#### SAMSUNG

LED LH181B  
FWHM / FWTM 31.0° / 53.0°  
Efficiency 92 %  
Peak intensity 2.7 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



#### SAMSUNG



LED LH351B  
FWHM / FWTM 32.0° / 53.0°  
Efficiency 94 %  
Peak intensity 2.7 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:




### PHOTOMETRIC DATA (MEASURED):

#### SAMSUNG


LED LH351Z  
FWHM / FWTM 34.0° / 54.0°  
Efficiency 88 %  
Peak intensity 2.7 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



LED Z5  
FWHM / FWTM 32.0° / 51.0°  
Efficiency 86 %  
Peak intensity 3 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



LED Z5M1/Z5M2  
FWHM / FWTM 32.0° / 51.0°  
Efficiency 91 %  
Peak intensity 2.8 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:







### PHOTOMETRIC DATA (SIMULATED):




LED XP-E2  
FWHM / FWTM 31.0° / 51.0°  
Efficiency 95 %  
Peak intensity 3.2 cd/lm  
LEDs/each optic 1  
Light colour Green  
Required components:




LED XP-G2  
FWHM / FWTM 32.0° / 53.0°  
Efficiency 94 %  
Peak intensity 3 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



LED XP-G3  
FWHM / FWTM 31.0° / 56.0°  
Efficiency 94 %  
Peak intensity 2.6 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:




LED XT-E  
FWHM / FWTM 31.8° / 53.5°  
Efficiency 94 %  
Peak intensity 2.8 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



### PHOTOMETRIC DATA (SIMULATED):


#### LUMILEDS

LED LUXEON SunPlus 20 Line (120 deg)  
FWHM / FWTM 31.0° / 52.0°  
Efficiency 95 %  
Peak intensity 3.1 cd/Im  
LEDs/each optic 1  
Light colour White  
Required components:




#### LUMILEDS

LED LUXEON SunPlus 20 Line (150 deg)  
FWHM / FWTM 31.0° / 51.0°  
Efficiency 91 %  
Peak intensity 2.9 cd/Im  
LEDs/each optic 1  
Light colour White  
Required components:




#### LUMILEDS

LED LUXEON Z ES  
FWHM / FWTM 30.0° / 50.0°  
Efficiency 94 %  
Peak intensity 3.4 cd/Im  
LEDs/each optic 1  
Light colour White  
Required components:



#### NICHIA

LED NCSxE17A  
FWHM / FWTM 32.0° / 62.0°  
Efficiency 87 %  
Peak intensity 2.1 cd/Im  
LEDs/each optic 4  
Light colour White  
Required components:




### PHOTOMETRIC DATA (SIMULATED):

#### OSRAM

Opto Semiconductors


LED OSCONIQ P 3030  
FWHM / FWTM 32.0° / 51.0°  
Efficiency 97 %  
Peak intensity 3.1 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



#### OSRAM


Opto Semiconductors

LED OSLOM Square EC  
FWHM / FWTM 32.0° / 52.0°  
Efficiency 94 %  
Peak intensity 2.9 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:




#### SAMSUNG

LED LM28xB Series  
FWHM / FWTM 31.0° / 53.0°  
Efficiency 94 %  
Peak intensity 2.7 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



SEOUL SEMICONDUCTOR

LED Z8Y22P  
FWHM / FWTM 32.0° / 55.0°  
Efficiency 94 %  
Peak intensity 2.7 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B  
Casic Motor Building  
Shenzhen 518057  
P.R.CHINA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Salo, Finland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)